



Mobilgard™ 410 NC

ExxonMobil Marine , Caribbean

Marine Crankcase Oil

Product Description

Mobilgard 410 NC (No Chlorine) engine oil is a non-zinc and non-chlorine lubricant specifically formulated with a Progress Rail (EMD) and General Electric (GE) endorsed additive technology to meet requirements of heavily loaded diesel engines manufactured by EMD and used in marine applications.

Its alkalinity reserve provides excellent corrosion protection when using fuels containing up to 0.05 wt.% sulfur, even though metals such as steel, copper, silver, and bronze are present. It has excellent lubricating properties and has high viscosity index to help reduce oil consumption and is optimized for low and ultra-low sulfur fuel use and is LNG, biofuel, and Tier IV engine ready.

Features and Benefits

Mobilgard 410 NC was developed by ExxonMobil to meet performance requirements of Tier IV engines.

Engineered to combat sludge and deposits formation while extending oil life in intermittent marine services, providing clean, smooth-running engines. Advanced dispersant technology provides high soot loading capability leads to excellent cleanliness in engines with lower lube oil consumption rates.

Formulated to improved anti-wear protection and load carrying properties, helps to protect critical wear surface and extend engine life. Optimized TBN and sulfated ash content for use with low and ultra-low sulfur diesel fuel and is biofuel and LNG ready.

Features	Advantages and Potential Benefits
High thermal and oxidation stability.	Extended oil drain intervals.
Excellent TBN reserve and retention.	Combat fuel/combustion related corrosion and deposits.
Effective wear protection.	Reduce wear to prolong engine life.
Advanced dispersant technology	Lower lube oil consumption rates.

Applications

- Heavily loaded diesel engines manufactured by EMD/GE and used in marine applications.
- Marine diesel engines of the highest horsepower, or higher brake mean effective pressure (BMEP) using distillate fuels with a sulfur content up to 0.05 wt.%
- Diesel engines manufactured by Alco, Detroit Diesel, and Fairbanks Morse

Specifications and Approvals

This product has the following approvals:
LMOA Gen 7 - Fundamental Approval (letter on file)

This product has the following approvals:

Progress Rail Worthy of Field Test (recognition letter on file)

Properties and Specifications

Property	
Grade	SAE 40
Flash Point, °C, ASTM D92	266
Ash, Sulfated, mass%, ASTM D874	1.1
Viscosity Index, ASTM D2270	104
Pour Point, °C, ASTM D97	-24
Zinc, mg/kg, ASTM D5185	<0.5
Density @ 15 C, kg/l, ASTM D4052	0.897
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.2
Base Number, mgKOH/g, ASTM D2896	11
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	148

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil Marine Limited
 Ermyn Way
 Leatherhead, Surrey
 United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved