



Flexxipave I-D

ExxonMobil Specialties , 中国

Flexxipave I-D is a polymer modified asphalt

Product Description

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Application

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

| Property | Min | Max |
|---|-----|-----|
| Penetration, 25C, 100g, 5s, 0.1mm, T0604 | 40 | 60 |
| Softening Point, R&B, °C, T0606 | 60 | |
| Ductility @5C, 5cm/min, cm, T0605 | 20 | |
| Flash Point, °C, T0611 | 230 | |
| Elastic Recovery, 25C, %, T0662 | 75 | |
| Retained penetration ratio on RTFOT(T0610) Residue, 25C, %, T0604 | 65 | |
| Ductility @5C on RTFOT(T0610) Residue, cm, T0605 | 15 | |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Asia Pacific Ltd

1 HarbourFront Place

#06-00 HarbourFront Tower One


Singapore 098633

+65 6885 5000

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved