



Mobilgard™ HSD CF4

ExxonMobil Marine , Malaysia

High Speed Diesel Engine Oil

Product Description

Mobilgard™ HSD CF-4 variants, 15W-40 and 20W-50 are diesel engines oils that provide proven protection of diesel engines operating in marine service applications. Mobilgard HSD CF-4 engine oils are recommended by ExxonMobil for use in a wide range of diesel engines for use in a variety of operating environments in marine industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up
TBN reserve	Deposit control
Component compatibility	Long seal and gasket life

Applications

Mobilgard HSD CF-4 oils, 15W-40 and 20W-50 are designed to provide proven engine protection for marine diesel engines, including those models typically used in industries such as inland, coastal, fishing, dredging, offshore service and other similar applications.

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
API CF-4	X	X

Properties and Specifications

Property	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1	1
Density @ 15 C, g/ml, ASTM D1298	0.87	0.88
Flash Point, Cleveland Open Cup, °C, ASTM D92	239	241
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.9	18.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	114	162

Property	MOBILGARD HSD 15W-40 CF-4	MOBILGARD HSD 20W-50 CF-4
Pour Point, °C, ASTM D97	-30	-27
Total Base Number, mgKOH/g, ASTM D2896	9.1	9.1

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2023

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved