



MOBIL 1 HYBRID 0W-20

Mobil Passenger Vehicle Lube , Central America

Advanced Full Synthetic Engine Oil

Product Description

Keep your hybrid engine running like new. Mobil 1 Hybrid full synthetic motor oil is specially formulated for hybrid engines and their unique technical needs. Hybrid engines run differently than non-hybrid (internal combustion) engines - they generally run at lower operating temperatures as the power source rotates between the engine and battery. These lower operating temperatures can allow contaminants, like fuel and water, to accumulate in the engine oil. Mobil 1 Hybrid is formulated with extra additives to help fight damage from these harmful contaminants and to provide that extra protection your hybrid engine needs. Mobil 1 Hybrid utilizes our signature Triple Action Formula to deliver performance, protection and cleanliness to your vehicle. This advanced formulation is engineered to protect for 15,000 miles between oil changes* and to help enhance fuel economy. Mobil 1 Hybrid meets ILSAC GF-6 standards. Available in 1QT and 5QT bottles. Mobil 1 Hybrid is recommended by ExxonMobil for all types of hybrid vehicles - passenger cars, SUVs, light vans and light trucks. Mobil 1 is America's #1 selling synthetic motor oil brand at retail,** trusted and recommended by car builders and experienced mechanics, and is the Official Motor Oil of NASCAR®.

Features and Benefits

Mobil 1 Hybrid advanced full-synthetic motor oil 0W-20 is a low-viscosity product engineered to help enhance fuel economy.

Utilizes Mobil 1's signature Triple Action Formula to deliver outstanding engine performance, protection, and cleanliness

Protects for 15,000 miles between oil changes - Guaranteed*

Provides extra protection for hybrid engines with extra additives to help fight damage from harmful contaminants

Provides 10% improved emissions system protection** for these modern engines.

Applications

* Protects for 15,000 miles or 1 year, whichever comes first

**Vs our Mobil 1 API SN Plus product

***Source: The NPD Group/ Retail Tracking Service/ Dollar Sales/ 52 weeks ending May 28, 2022

Specifications and Approvals

This product has the following approvals:

GM dexos1:GEN3 Licensed

This product is recommended for use in applications requiring:

Ford WSS-M2C947-A

Ford WSS-M2C947-B1

This product meets or exceeds the requirements of:

API SJ

API SL

API SM

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

ILSAC GF-6A

Chrysler MS-6395

FORD WSS-M2C962-A1

Properties and Specifications

Property	
Grade	SAE 0W-20
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	43.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.2
Density @ 15.6 C, g/ml, ASTM D4052	0.851
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

ExxonMobil de Colombia S.A.

Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved