



MOBIL GS 333 PLUS

Mobil Passenger Vehicle Lube , Chile  
Antifreeze Anticorrosive Fluid for Radiator Water

Product Description

Antifreeze anticorrosive fluid specially developed for Mercedes-Benz. Formulated on a monoethylene glycol basis, to be added to the water of the cooling systems of Mercedes-Benz gasoline or diesel engines. Does not attack sealing joints or interfere with heat transfer.

Features and Benefits

| Features  | Advantages and Potential Benefits   |
|---|---|
| Raises the boiling point and lowers the freezing point of the radiator water. |   |
| Effective corrosion protection, especially rust.                              |   |
| It does not attack rubbers and gaskets.                                       |   |
|   | Increases the boiling temperature and reduces the freezing temperature of the radiator water. |
|   | Protects the radiator from rust and corrosion.  |
|   | Compatible with metals and metal alloys used in the vehicle cooling system.                   |

Applications

Approved by Mercedes-Benz as per page 325.0 for use in gasoline and diesel engine cooling systems. For the use of Mobil® GS 333 Plus exhaust the water from the cooling system, preferably with the heated engine, and if necessary circulate a good detergent for radiators in order to promote its degrease. As a service information, prepare the solution with Mobil® GS 333 Plus, outside the system, adding the product to the water until it reaches the concentration recommended by truck and bus manufacturers. Then place this solution on the radiator.

Specifications and Approvals

|  |
|--|
| This product has the following approvals:          |
| MB-Approval 325.0                                  |
| This product meets or exceeds the requirements of: |
| GME B 040 0240                                     |
| SAAB 6901599                                       |

Properties and Specifications

|          |  |
|----------|--|
| Property |  |
|----------|--|

| Property                                 |              |
|--|--------------|
| Freeze Point (33% volume), C, ASTM D1177 | -15          |
| pH value @ 25 C, ASTM D1287              | 7.2          |
| Refractive Index 20 C, DIN 51423         | 1.433        |
| Reserve Alkalinity, ml, ASTM D1121       | 14           |
| Appearance, Visual                       | Clear Liquid |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023  
COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO  
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved