



## Mobil Super 1000 10W-30 and 20W-50

Mobil Passenger Vehicle Lube , Colombia

Premium Multigrade Passenger Vehicle Engine Oils

### Product Description

Mobil Super 1000 10W-30 and 20W-50 are premium quality mineral motor oils meeting the latest industry engine oil specifications. They are designed to provide a high level of performance and protection under most operating conditions.

### Features and Benefits

Engine protection during start up

Extended protection against engine wear and deposits formation

Helps combat sludge

Mobil Super 1000 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps promote long engine life.

### Applications

Mobil Super 1000 10W-30 and 20W-50 have been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super 1000 for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product is recommended for use in applications requiring:	10W-30	20W-50
API CF	X	
API Energy Conserving (SM)	X	
ILSAC GF-4	X	

This product meets or exceeds the requirements of:	10W-30	20W-50
API SJ	X	
API SL	X	X
API SM	X	
API SN	X	

This product meets or exceeds the requirements of:	10W-30	20W-50
API SN Resource Conserving	X	

### Properties and Specifications

Property	10W-30	20W-50
Grade	SAE 10W-30	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0.8	0.8
Density @ 15 C, g/ml, ASTM D4052		0.8928
Flash Point, Cleveland Open Cup, °C, ASTM D92	220	240
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.2	
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683		4.7
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	10.5	19
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	65.5	174
Pour Point, °C, ASTM D97	-36	-27
Viscosity Index, ASTM D2270	149	124

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved