



Mobil Special 2T

Mobil Passenger Vehicle Lube , Egypt  
High Performance Two-Stroke Engine Oil

Product Description

Mobil Special 2T is a high performance, two-stroke engine oil for use in motorcycles, snowmobiles and lean oil/fuel ratio chain saws. Mobil Special 2T is pre-diluted to ensure rapid mixing when added to fuel.

Features and Benefits

Mobil Special 2T combines quality mineral oils with an excellent additive system to provide good overall cleaning and performance. Key features and benefits include:

| Features                                                                                               | Advantages and Potential Benefits                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Good wear protection                                                                                   | Longer engine life                                                                                                                                                                                                                                                                                                                  |
| Thermal and oxidation stability and d<br>e<br>p<br>o<br>s<br>i<br>t<br>c<br>o<br>n<br>t<br>r<br>o<br>l | Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking and piston tightening as w<br>e<br>l<br>l<br>a<br>s<br>p<br>r<br>o<br>t<br>e<br>c<br>t<br>i<br>o<br>n<br>a<br>g<br>a<br>i<br>n<br>s<br>t<br>p<br>r<br>e<br>-<br>i<br>g<br>n<br>i<br>t<br>i<br>o<br>n<br>p<br>r<br>o<br>b<br>l<br>e<br>m<br>s |
| Good corrosion protection properties                                                                   | Longer engine life                                                                                                                                                                                                                                                                                                                  |
| Reduces pre-ignition                                                                                   | Improved fuel efficiency and extended piston life                                                                                                                                                                                                                                                                                   |

Applications

Mobil Special 2T is recommended by Exxonmobil for use two-stroke engines where JASO FB level performance is recommended.

Specifications and Approvals

|                                                        |    |
|--------------------------------------------------------|----|
| Mobil Special 2T meets or exceeds the requirements of: |    |
| JASO                                                   | FB |

Typical Properties

| Viscosity, ASTM D 445            |       |
|----------------------------------|-------|
| cSt @ 40° C                      | 63    |
| cSt @ 100° C                     | 8.7   |
| Viscosity Index, ASTM D 2270     | 110   |
| Sulfated Ash, wt%, ASTM D 874    | 0.05  |
| Pour Point, °C, ASTM D 97        | -12   |
| Flash Point, °C, ASTM D 92       | 132   |
| Density @15° C kg/l, ASTM D 4052 | 0.878 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Special 2T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved