



## Mobil Delvac Modern™ 15W-40 Super Defense V4

Mobil Commercial Vehicle Lube , Israel

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac Modern 15W-40 Super Defense V4 is a high performance synthetic technology diesel engine oil that provides excellent lubrication of today's diesel engines promoting long engine life. As a result, this product meets or exceeds the requirements of virtually all major European and American engine manufacturers. The chemistry of this product provides excellent performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high Sulphur fuel. Mobil Delvac Modern 15W-40 Super Defense V4 combines a blend of high performance base stocks with a balanced additive system to provide excellent control of oil thickening due to soot build-up and high temperatures as well as excellent resistance to oxidation, corrosion, and high temperature deposits

### Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure and retarded timing require improved oil performance in areas such as oxidation stability, soot dispersancy, and volatility. Mobil Delvac Modern 15W-40 Super Defense V4 is formulated from high performance base oils and a balanced additive system to contribute to optimum engine performance in modern diesel and gasoline engines as well as older models. The key potential benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Long oil life and cleaner engines
TBN reserves	Deposit control and acid neutralization
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability

### Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Mixed fleet applications

### Specifications and Approvals

This product has the following approvals:
Detroit Fluids Specification 93K215
DTFR 15B110

**This product has the following approvals:**

RENAULT TRUCKS RLD-2

Mack EO-N

Mack EO-M Plus

VOLVO VDS-3

Cummins CES 20076

Cummins CES 20077

**This product is recommended for use in applications requiring:**

API CF

ACEA B2

API CF-4

VOLVO VDS-2

API CG-4

Mack EO-M

RENAULT TRUCKS RLD

MAN M 3275-1

Cummins CES 20071

Cummins CES 20072

**This product meets or exceeds the requirements of:**

ACEA E7

API SL

API SJ

MTU Oil Category 2

Ford WSS-M2C171-D

Caterpillar ECF-2

API CH-4

API CI-4

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Ash, Sulfated, mass%, ASTM D874	1.1
Cold-Cranking Simulator, Apparent Viscosity @ -20 C, mPa.s, ASTM D5293	5800
Density @ 15 C, kg/m3, ASTM D4052	0.87
Viscosity Index, ASTM D2270	136
Total Base Number, mgKOH/g, ASTM D2896	9.2
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.6
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	110

#### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved