



Mobil Super™ 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50

Mobil Passenger Vehicle Lube , Peru

High Performance Four-Stroke Motorcycle Engine Oil

Product Description

Mobil Super™ 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50 are high performance conventional four-stroke motorcycle engine oils primarily intended for general use in all types of four-stroke motorcycles and engines.

Features and Benefits

Mobil Super 4T 10W-30, 10W-40, 15W-40, 20W-40, 15W-50 and 20W-50 combine highly refined, quality mineral oils and an advanced additive system to provide good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps extend engine life
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Good corrosion protection	Protects critical engine components
Broad viscosity range	Year round engine protection and performance

Specifications and Approvals

Mobil Super 4T meets or exceeds the requirements of:	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
API			SJ			SJ
JASO	MA2	MA2	MA2	MA2	MA2	MA2

Mobil Super 4T is recommended by ExxonMobil for use in applications requiring:	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
API	SG	SG	SG	SG/CD	SG/CD	SG

Typical Properties

Mobil Super 4T	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
SAE Grade	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
Viscosity, ASTM D445						
cSt @ 40°C	70	100	108	118	165	167
cSt @ 100°C	10.8	14.5	14.5	14	16.8	18.8
Sulfated Ash, wt%, ASTM D874	0.96	0.91	0.99	0.85	0.97	0.96
Pour Point, °C, ASTM D97	-30	-30	-27	-27	-36	-24
Flash Point, °C, ASTM D92	226	222	223	230	224	242

Mobil Super 4T	10W-30	10W-40	15W-40	20W-40	15W-50	20W-50
Density @15.6°C g/ml, ASTM D4052	0.87	0.86	0.88	0.89	0.86	0.89

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Super 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020
Terpel Comercial del Perú S.R.L.
Av. Jorge Basadre Grohmann 347,
Interior 1005, San Isidro
Lima, Perú
24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved