



EHC™ Series

ExxonMobil Basestocks , Canada

Product Description

EHC base stocks by ExxonMobil are designed for performance capability in a broad range of finished lubricant applications. With base oil interchange and viscosity read-across capabilities, ExxonMobil's EHC base stock slate offers broad coverage, enabling supply chain flexibility and simplified qualification testing require ExxonMobil follows rigorous processes to ensure reliable delivery of consistent quality base stocks so customers can be confident in their base stock supply. EHC stocks by ExxonMobil comprise a global Group II slate as defined within API and ATIEL guidelines for formulation and qualification of automotive lubricants.

EHC base stocks by ExxonMobil may also be utilized in Industrial and Marine applications where formulations benefit from the increased oxidation stability and high

Features and Benefits

- EHC base stocks deliver qualities that enable our customers to produce high performance blends. Key features include:
- Tightly controlled volatility and viscosity index (VI) specifications enabling formulations to meet or exceed API, ACEA and ILSAC requirements
  - Targeted saturates levels to provide optimum additive solubility
  - Exceptional oxidation stability
  - Product specifications that enable formulators to meet or exceed passenger and heavy-duty engine oil quality requirements.

Specifications

Property	Standard Method(a)	Limits	EHC 45	EHC 50	EHC 65	EHC 110	EHC 120	EHC MAX
ASTM Color	ASTM D1500	Max	L0.5	0.5	L0.5	0.5	0.5	L1.5
Appearance	Visual	Min-Max	Clear and Bright	Clear and Bright	Clear and Bright	Clear and Bright	Clear and Bright	Clear and Bright
Cold-Cranking Simulator, Apparent Viscosity @ -20 C,mPa.s	ASTM D5293	Max		1,500	3,100			
Cold-Cranking Simulator, Apparent Viscosity @ -25 C,mPa.s	ASTM D5293	Max	1,550					
Flash Point, Cleveland Open Cup,°C	ASTM D92	Min	204	210	214	230	255	294
Kinematic Viscosity @ 100 C,mm2/s	ASTM D445	Min-Max	4.4-4.7	5.2-5.6	6.3-6.6	10.0-12.0	11.7-12.5	32.5-35
Kinematic Viscosity @ 40 C,mm2/s	ASTM D445	Min-Max					96-108	460-520
Noack Volatility, Procedure B,mass%	ASTM D5800-PROB	Max	14.5	13.5	10			
Pour Point,°C	ASTM D97	Max	-18	-18	-18	-15	-15	-15
Saturates,wt%	ASTM D7419	Min						98
Viscosity Index	ASTM D2270	Min-Max	113-119	110-119	103-109	95-110	102-115	95-115

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

(b)EHC 340 MAX to be commercially available starting in 2025.

**Health and Safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

The information contained herein is subject to change without notice. Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same. All products may not be available locally. For more information, contact your local Imperial Oil contact or visit [www.imperialoil.ca](http://www.imperialoil.ca).

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved