E∕∕onMobil

Mobilgard HSD 15W-40 CF-4

ExxonMobil Marine , 中国

Product Description

Mobilgard HSD 15W-40 CF-4 is a performance diesel engine oil that provides proven protection of diesel engines operating in marine service applications. Mol HSD 15W-40 CF-4 is recommended by ExxonMobil for use in a wide range of diesel engines for use in a variety of operating environments in marine industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up
TBN reserve	Deposit control
Component compatibility	Long seal and gasket life

Applications

Mobilgard HSD 15W-40 CH-4 is designed to provide proven engine protection for marine diesel engines, including those models typically used in industries s Inland, coastal, fishing, dredging, offshore service and other similar applications.

Specifications and Approvals

This produc	ct is recommended for use in applications requiring:
API CF-4	

Properties and Specifications

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-39
Viscosity Index, ASTM D2270	136
Density @ 15 C, kg/l, ASTM D4052	0.88
Total Base Number, mgKOH/g, ASTM D2896	6
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	104
Ash, Sulfated, mass%, ASTM D874	0.73
Flash Point, Cleveland Open Cup, °C, ASTM D92	232

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2023 ExxonMobil Marine Limited Ermyn Way Leatherhead, Surrey United Kingdom KT22 8UX

http://www.exxonmobil.com

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

