



Prowax 900

ExxonMobil Specialties , Guinea

Product Description

Prowax 900 is a wax product, that is a translucent soft solid at low temperatures and a clear liquid when molten. It is derived from petroleum via a carefully controlled refining process and is primarily comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowax 900 is typically used in the following applications subject to applicable laws and regulations in each jurisdiction*:

- De-dusting for roofing granules, roads, fertilizer, glass wool, and textile treating
- Wax emulsions
- Wax blends

* User must check compliance with applicable regulations

Properties and Specifications

Property	Standard Method(a)	Typical	Min	Max
Density, @ 85°C (185°F), kg/m ³	ASTM D 1298	800		
Density, @ 15°C (59°F), kg/m ³ (b)	ASTM D 1298	857		
Flash Point COC, °C (°F)	ASTM D 92		156(313)	

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

(b) Density at 15°C is based on measurement of the wax liquid density at a higher temperature corrected to 15°C using ASTM D1250 Table B.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com

Further Information

ExxonMobil supplies a full range of waxes, white oils, process oils, asphalt and a full range of lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.ExxonMobil.com, for more information on other products.

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

ExxonMobil Lubricants & Specialties Europe

Hermeslaan 2

1831 Machelen

BELGIUM

+32-2-722-2111

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved