



## PAVING ASPHALT 60/70 TPI

ExxonMobil Asphalt, Indonesia

PENETRATION GRADED ASPHALT PRODUCT

### Product Description

Paving Asphalt 60/70 TPI is a penetration graded asphalt product. The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third Party supplier.

### Applications

Paving Asphalt 60/70 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

### Properties and Specifications

Property	Standard Method(a)	Limit	
Penetration, 25 C, 0.1 mm	ASTM D5	Min-Max	60-80
Softening Point, °C	ASTM D36	Min	46
Flash Point, Cleveland Open Cup, °C	ASTM D92	Min	232
Solubility in Trichloroethylene, wt%	ASTM D2042	Min	99.0

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved

