



Mobil Jet™ Oil CI

ExxonMobil Aviation , Kuwait

Advanced Full Synthetic Turbine Oil

Product Description

Mobil Jet™ Oil CI is a high performance aircraft-type gas turbine lubricant, based upon the proven Mobil Jet Oil II formulation technology that has been updated to include additional additives for improved protection against rust and corrosion in severe operating environments. It is fully qualified against the Corrosion Inhibited classification in the MIL-PRF-23699 specification and approved for use in military and commercial applications that require this level of performance.

Features and Benefits

Mobil Jet Oil II is formulated to meet the demanding requirements of aircraft-type gas turbines operating over a wide range of severe operating conditions, including severe salt water corrosive environments.

| Features  | Advantages and Potential Benefits   |
|---|---|
| Excellent thermal and oxidation stability                         | Helps reduce the formation of carbon and sludge deposits<br>Maintains engine efficiency and extends engine life |
| Excellent corrosion protection                                    | Protects against rust and corrosion<br>Helps extend gear and bearing life                                       |
| Retains viscosity and film strength across wide temperature range | Provides effective lubrication at high operating temperatures   |
| Chemically stable   | Helps reduce evaporation losses and lowers oil consumption  |
| Low pour point  | Eases start-up in low ambient temperature conditions  |

Applications

Mobil Jet Oil CI is recommended for aircraft gas turbine engines of the turbo-jet, turbo-fan, turbo-prop, and turbo-shaft (helicopter) types in commercial and military service. It is also recommended for aircraft-type gas turbine engines used in industrial or marine applications where additional protection against salt water corrosion is required. Mobil Jet Oil CI is approved against the Corrosion Inhibited (CI) classification of U.S. Military Specification MIL-PRF-23699. It is also compatible with synthetic gas turbine lubricants meeting MIL-PRF-23699. However, mixing with other products is not recommended because the blend would result in some loss of performance characteristics of Mobil Jet Oil CI. Mobil Jet Oil CI is compatible with all metals used in gas turbine construction, as well as with F Rubber (Viton®), Rubber (Buna N), and silicone seal materials.

Specifications and Approvals

|  |
|--|
| <b>This product has the following approvals:</b> |
| MIL (US) MIL-PRF-23699-CI                        |

Properties and Specifications

| Property                                    |     |
|---|-----|
| Color, ASTM D1500                           | 3.5 |
| Foam, Sequence III, Tendency, ml, ASTM D892 | 0   |

| Property   |       |
|--|-------|
| Change in Kinematic Viscosity, 72 h @ -40 C, %, ASTM D2532 | 1     |
| Water, ppm, ASTM E1064                                     | 70    |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445              | 5     |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445               | 25    |
| Kinematic Viscosity @ -40 C, mm2/s, ASTM D445              | 10690 |
| Total Acid Number, mgKOH/g, ARP 5088                       | 0.27  |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 270   |
| Pour Point, °C, ASTM D5950                                 | -63   |
| Evaporation Loss, 6.5 h, 204 C, mass%, ASTM D972(mod)      | 4.1   |
| Foam, Sequence I, Tendency, ml, ASTM D892                  | 0     |
| Foam, Sequence II, Tendency, ml, ASTM D892                 | 0     |
| Phosphorus, mg/kg, ASTM D5185                              | 2740  |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved