Prowax 312 Page 1 of 2

# **E**xonMobil

# Prowax 312

ExxonMobil Specialties, Mexico

### Product Description

Prowax 312 is a low-range melting point product in the Prowax line of petroleum slack and scale waxes. It is a translucent crystalline material in the solid state and a white-to-straw yellow, clear liquid when molten. It is derived from petroleum via a carefully controlled refining process. Prowax 312 is comprised of a mixture of s chain normal paraffin and branched, iso-paraffin hydrocarbons.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

# **Applications**

Prowax 312 can be used in the following applications subject to applicable laws and regulations in each jurisdiction\*

- Candles
- Wax emulsions
- Wax blends

#### **Properties and Specifications**

Property	Standard Method(a)	Min	Мах
Melting Point, °C	ASTM D87	50.0	56.0
Oil Content, wt%	ASTM D721		6.0
ASTM Color by Auto Tristimulus	ASTM D6045		1.0
Kinematic Viscosity @ 100 C, mm2/s	ASTM D445	2.7	4.1
Flash Point, Cleveland Open Cup, °C	ASTM D92	200	

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant dig in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

# Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil Mexico, S.A. de C.V.
Poniente 146 No. 760 Col. Industrial Vallejo
C.P. 02300 Mexico, Ciudad de Mexico
http://www.exxonmobil.com
(01 52) 55 5-333-9602 (01 52) 1-800 90-739-00

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied

<sup>\*</sup> User must check compliance with applicable regulations

Prowax 312 Page 2 of 2

the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

