



Paving Bitumen EM Series

ExxonMobil Asphalt, Netherlands

PENETRATION GRADED BITUMEN PRODUCTS - NETHERLAND

Product Description

Paving Bitumen EM are penetration graded bitumen products derived from specially selected crude oils via carefully controlled refining processes.

The quality of ExxonMobil products is assured for every delivery. They are produced and controlled according to the ExxonMobil Global Product Integrity Management System, EN ISO 9000 or equivalent standard.

Applications

Paving Bitumen EM grades are recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties & Specifications

Paving Bitumen EM grades meet both the NEN EN 12591:2009 specifications requirements:

Paving Bitumen grades			35/50 EM	40/60 EM	50/70 EM	70/100 EM	100/150 EM	160/220 EM
Property	Unit	Test Method						
Penetration at 25°C	x 0.1 mm	EN 1426	35-50	40-60	50-70	70-100	100-150	160-220
Softening point	°C	EN 1427	50-58	48-56	46-54	43-51	39-47	35-43
Flash point (min)	°C	ISO 2592	240	230	230	230	230	220
Solubility in toluene (min)	% (m/m)	EN 12592	99.0	99.0	99.0	99.0	99.0	99.0
Kinematic viscosity at 135°C (min)	mm ² /s	EN 12595	370	325	295	230	175	135
Fraass breaking point (max)	°C	EN 12593	-5	-7	-8	-10	-12	-15

Resistance to hardening: Rolling Thin Film Oven Tests at 163 °C (EN 12607-1)

Change of mass (max) +/-	%	EN 12607-1	0.5	0.5	0.5	0.8	0.8	1.0
Retained penetration (min)	%	EN 1426	53	50	50	46	43	37
Increase in softening point - Severity 1 (max)	°C	EN 1427	8	9	9	9	10	11

Both the NEN EN 12591 specifications may be subject to change.

Paving Bitumen EM grades delivered in Netherlands meet only the Dutch NEN EN 12591 specifications.

Health & Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.exxonmobil.com for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

