



# Mobil Avrex M Turbo 201/1010

ExxonMobil Aviation , Saudi Arabia

Aircraft Type Gas Turbine Lubricant

## Product Description

Mobil Avrex M Turbo 201/1010 gas turbine lubricant is a combination of a proven aviation engine mineral oil base stock and an ashless additive package. The effective operating range for Mobil Avrex M Turbo 201/1010 is between -40°C and 121°C (-40°F and 250°F). The pour point is below -51°C (-70°F).

## Applications

Mobil Avrex M Turbo 201/1010 is recommended for older design aircraft gas turbine engines. This product is approved against U.S. Military Specification MIL-PRF-6081, Grade 1010. It should be used only in those turbine engines where the operating temperatures are within the capability range of mineral oil-based lubricants.

## Typical Properties

| Avrex M Turbo 201/1010 |           | MIL-PRF-6081 Requirements |
|------------------------|-----------|---------------------------|
| Product Number         | 49411-2   | -                         |
| Viscosity              |           |                           |
| cSt at 100°C (212°F)   | 2.6       | -                         |
| cSt at 40°C (104°F)    | 10.4      | 10.0 min                  |
| cSt at -40°C (-40°F)   | 2,818     | 3,000 max                 |
| Flash Point, °C (°F)   | 145 (293) | 132 (270) min             |
| Pour Point, °C (°F)    | -60 (-75) | -57 (-70) max             |

|                                     |       |          |
|-------------------------------------|-------|----------|
| Specific Gravity, 15/15°C (60/60°F) | 0.885 | -        |
| TAN, mg KOH/g                       | 0.03  | 0.10 max |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health w used for the intended application and the recommendations provided in the Material Safety Data SI (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via Internet. This product should not be used for purposes other than its intended use. If disposing of l product, take care to protect the environment.

The ExxonMobil logotype, Mobil and Avrex M Turbo are trademarks of Exxon Mobil Corporation, or of its subsidiaries. PDSAV-12

05-2020

Exxon Mobil Corporation  
22777 Springwoods Village Parkway  
Spring TX 77389

For additional technical information or to identify the nearest U.S. ExxonMobil supply source, cal 800 662-4525.

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subjec change without notification. Typical Properties may vary slightly.

ExxonMobil

Exxon

Mobil

Esso

XT

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved