



Waxrex 715

ExxonMobil Specialties , Slovakia

Product Description

Waxrex 715 is a high quality saturating wax for corrugated paperboard. It is a translucent crystalline material in the solid state and an essentially water white, clear liquid when molten. Waxrex 715 comprises a blend of refined paraffin waxes and a carefully selected additive system. Application of this product to corrugated packaging imparts excellent water resistance, high compressive strength in both wet and dry service, scuff resistance and good score line flexibility. A high blocking point minimizes the tendency for blockage during shipping and storage of finished saturated cartons. Waxrex 715 meets applicable Food and Drug Administration (FDA) requirements for food-related uses.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Waxrex 715 is primarily used in the following applications subject to applicable laws and regulations in each jurisdiction*:

- Wax coating for corrugated paper cartons
- Wax coating for paper packaging

* User must check compliance with applicable regulations

Properties and Specifications

Waxrex 715 meets applicable Food and Drug Administration (FDA) requirements for food, health and cosmetic- related uses as noted below:

21 CFR 176.170 Components of paper and paperboard in contact with aqueous and fatty foods;

21 CFR 176.180 Components of paper and paperboard in contact with dry food; and

21 CFR 175.105 Adhesives as components of articles intended for use in packaging, transporting or holding of food.

Batch Release Tests	Units	Methods	Min	typ	max
Density @15°C	kg/m3	ASTM D1298	-	817	-
ATSM Saybolt D156 Color	none	ASTM D6045	15	-	-
Congealing Point	°C (F)	ASTM D87	52.8(127)	55.0(131)	57.2(134.9)
Odor,Wax	none	ASTM D1833	-	-	1
Appearance (Molten)	none	VISUAL	-	-	-
Kinematic Viscosity (@100C)	cSt	ASTM D445		4.7	
Cloud Point	°C (F)	AM-S 1419		76.1(169)	-
Sales Specifications			-	-	-
Flash Point, COC	°C (F)	ASTM D92	204(400)	-	-

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

(b) Density at 15°C is based on measurement of the wax liquid density at a higher temperature corrected to 15°C using ASTM D1250 Table B.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com

Further Information

ExxonMobil supplies a full range of waxes, white oils, process oils, asphalt and a full range of lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.ExxonMobil.com, for more information on other products.

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

ExxonMobil Lubricants & Specialties Europe

Hermeslaan 2

1831 Machelen

BELGIUM

+32-2-722-2111

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved