



## Mobil Delvac MX™ ESP 10W-30

Mobil Commercial Vehicle Lube , Austria

### Product Description

Mobil Delvac MX ESP 10W-30 is an extra high performance diesel engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, Mobil Delvac MX ESP 10W-30 will also delivers excellent performance in older conventional engines. As a result, it meets or exceeds the requirements of API CK-4, CJ-4, CI-4 PLUS and CH-4 service categories as well as key Original Equipment Manufacturer (OEM) requirements.

Mobil Delvac MX ESP 10W-30 is the result of extensive cooperative development work with major OEMs and is recommended by ExxonMobil for use in a wide range of heavy duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries. This product provides outstanding protection in the most demanding diesel engines including those Volvo engines requiring oils meeting the VDS-4.5 specification. Mobil Delvac MX ESP 10W-30 also meets or exceeds the requirements of the API SN specification for gasoline engines and mixed fleets.

### Features and Benefits

Mobil Delvac MX ESP 10W-30 is formulated with Trimer additive technology and a mixed detergent system to deliver cutting-edge performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and outstanding Total Base Number (TBN) retention for long drain intervals, Mobil Delvac ESP 10W-30's advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

#### The key benefits include:

| Features   | Advantages and Potential Benefits  |
|--|--|
| Superior soot-viscosity control  | Helps to maintain engine efficiency, long engine life and long oil life  |
| Outstanding thermal and oxidative stability  | Helps to reduce low temperature sludge build-up and high temperature deposits                                    |
| Excellent oil consumption control  | Helps to lower oil costs due to less make-up oil during operation  |
| Excellent TBN reserves   | Helps to improve corrosion protection and to extend drain intervals  |
| Stay-in-grade shear stability  | Helps to maintain viscosity in severe, high temperature service for greater wear protection and long engine life |
| Excellent low temperature pumpability  | Fast oil flow and helps to reduce wear during engine start-up in low temperatures                                |
| Superb resistance to corrosive and abrasive wear   | Long life of critical wear surfaces  |
| Component compatibility  | Long gasket, seal, and after treatment (DPF and DOC) life  |
| Meets or exceeds demanding specifications of key OEMs and latest API gasoline service category | One engine oil for mixed fleet operations  |

### Applications

Recommended by ExxonMobil for use in:

- The latest low-emissions, high performance diesel applications equipped with aftertreatment systems using Diesel Particulate Filter (DPF) and Diesel

Oxidation Catalyst (DOC) technologies.

- High-performance diesel applications including turbo-charged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.
- On-highway applications operating in both high speed/high load and short haul pick-up/delivery.
- Off-highway applications operating in severe low speed/heavy load conditions.
- High performance gasoline engines and mixed fleet operations.
- Diesel-powered equipment from American, European and Japanese OEMs

## Specifications and Approvals

|  |
|--|
| <b>This product has the following builder approvals:</b> |
| Detroit Detroit Fluids Specification 93K222              |
| Detroit Fluids Specification 93K218                      |
| MACK EOS-4.5   |
| MAN M 3575   |
| RENAULT TRUCKS RLD-3                                     |
| VOLVO VDS-4.5  |

|   |
|---|
| <b>This product is recommended for use in applications requiring:</b> |
| API CG-4  |
| API CF  |

|   |
|---|
| <b>This product meets or exceeds the requirements of the following industry and builder specifications:</b> |
| API CK-4  |
| API CJ-4  |
| API CI-4 PLUS   |
| API CI-4  |
| API CH-4  |
| API SN  |
| API SM  |
| CATERPILLAR ECF-3   |
| Cummins CES 20086   |
| ISUZU DEO (w/ DPD Equipped Vehicles)  |

**This product meets or exceeds the requirements of the following industry and builder specifications:**

JASO DH-2

**This product meets or exceeds the requirements of:**

ACEA E7

ACEA E9

## Properties and Specifications

| Property   |            |
|--|------------|
| Grade  | SAE 10W-30 |
| Ash, Sulfated, mass%, ASTM D874                            | 0.9        |
| Density @ 15 C, kg/l, ASTM D4052                           | 0.867      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 218        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 12         |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 82         |
| Pour Point, °C, ASTM D97                                   | -33        |
| Total Base Number, mgKOH/g, ASTM D2896                     | 9.6        |
| Viscosity Index, ASTM D2270                                | 140        |

## Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen


Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved