



Mobil Delvac™ MX Advanced City Logistics 5W-40

Mobil Commercial Vehicle Lube , Australia

Description

Mobil Delvac™ MX Advanced City Logistics 5W-40 is formulated to deliver high performance in commercial diesel engines equipped with a Diesel Particulate Filter (DPF) and is suitable for driving conditions of city logistics applications. Mobil Delvac™ MX Advanced City Logistics 5W-40 provides protection for DPFs and diesel engines under the conditions of frequent start-ups, stop and go driving in urban areas, and powerful driving for heavy loaded light commercial vehicles.

Features and Benefits

- Helps to maintain the efficiency of the Exhaust Emission Reduction systems in commercial vehicles.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in diesel engine light commercial vehicles.

Application

- Mobil Delvac™ MX Advanced City Logistics 5W-40 has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with most latest Diesel Particulate Filters
- Mobil Delvac™ MX Advanced City Logistics 5W-40 offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge and deposit build-up.

Specification

Mobil Delvac™ MX Advanced City Logistics 5W-40 meets or exceeds the requirements of:

ACEA C3

Typical Properties

Mobil Delvac™ MX Advanced City Logistics 5W-40	
Viscosity, ASTM D 445	
cSt @ 40° C	74.9
cSt @ 100° C	12.8
Sulfated Ash, wt%, ASTM D 874	0.8
Phosphorous, wt%, ASTM D 4951	0.08
Flash Point, °C, ASTM D 92	230
Density @15° C kg/l, ASTM D 4052	0.852
Pour Point, °C, ASTM D 97	-33

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

09-2019

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved