



Mobil Rarus™ PE R 220

Mobil Industrial , Belgium

Ethylene compressor oil

Product Description

Mobil Rarus™ PE R 220 is a premium ethylene compressor oil of ISO viscosity grade 220. It is a polymer thickened, food-grade white oil based lubricant used for the lubrication of ethylene hyper compressors.

In the production of polyethylene, high-speed reciprocating compressors are used to compress ethylene gas to high pressures up to 3000bar. In these applications, the compressor lubricant can come in contact with the polyethylene in the polymerization process. Under these circumstances, the lubricating oil required must be of acceptable purity and be known not to modify the properties of the polyethylene.

Mobil Rarus PE R 220 provides good lubrication of the compressor cylinders and is compatible with the polyethylene process. It can be used to produce polyethylene where food contact can occur such as in food packaging. Mobil Rarus PE R 220 offers good thermal and chemical stability.

Features and Benefits

Mobil Rarus PE R 220 is specifically engineered to help provide long and trouble-free compressor performance. Mobil Rarus PE R 220 is NSF H1 registered and meets the requirements of FDA regulation 21CFR 178.3570 for lubricants with potential for incidental food contact. Mobil Rarus PE R 220 also meets the requirements of FDA regulation 21 CFR 177.1520 for processing aids used in the production of olefin polymers intended for use in contact with food.

Mobil Rarus PE R 220 compressor oil offers the following benefits:

Features	Advantages and Potential Benefits
High neutrality and low reactivity components	Do not interfere with catalytic polymerization reactions
High purity components	Do not induce any discolouration or odor in the final polymer
Components approved for food contact	Suitable for the manufacture of polymers for food packaging
Low polarity	Suitable in the manufacture of polymers for electrical insulation and thin bags (plastic bags)
Premium quality product	Reduced maintenance shutdowns

- Suitable for applications where it can come in contact with food
- High purity levels so that it will not modify properties of polyethylene
- Excellent cylinder lubricant helping to prolong compressor life
- Good thermal and chemical stability resulting in lower deposits and longer oil life

Applications

Mobil Rarus PE R 220 has the following applications

- High pressure ethylene compressors
- Compressors used in the production of polyethylene used in food contact applications

Specifications and Approvals

Mobil Rarus PE R 220 meets or exceeds the requirements of:	
FDA 21 CFR 178.3570	X
FDA 21 CFR 177.1520	X

Mobil Rarus PE R 220 is registered to the requirements of:	
NSF H1	X
NSF Registration Number	141136

Typical Properties

Test Method	Test	Units	Mobil Rarus PE R22
ISO Viscosity grade			220
Density at 15°C	ASTM D4052	Kg/m3	871
Kinematic viscosity at 40°C	ASTM D 445	mm2/s	227
Colour, Saybolt	ASTM D156		+ 27 min
Flash Point	ASTM D 92	°C	210
Pour Point	ASTM D 97	°C	- 12 max
Acid number	ASTM D 974	mg KOH/g	0.05
Water content	ASTM D 6304	ppm	50

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved