



## Mobil 1™ ESP X3 0W-40

Mobil Passenger Vehicle Lube , Belgium

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ ESP X3 0W-40 is an advanced full synthetic engine oil specifically designed to provide outstanding performance for high powered engines, providing outstanding engine cleanliness, wear protection, strong durability and advanced fuel economy\*. Mobil 1 ESP X3 0W-40 is our latest technology developed in cooperation with Porsche, one of our key European Original Equipment Manufacturers (OEMs). Mobil 1 ESP X3 0W-40 has been expertly engineered to help prolong the life in new emerging gasoline powered European vehicles.

\*compared to our Mobil 1 ESP Formula 5W-30 / Mobil 1 ESP 5W-30

### Features and Benefits

Mobil 1 ESP X3 0W-40 is made with a proprietary blend of leading edge components formulated to be fully compatible with the latest Gasoline Particulate filters (GPF's). Mobil 1 ESP X3 0W-40 has been designed to help deliver outstanding performance and protection in conjunction with advanced fuel economy benefits. Key features and potential benefits include:

\*\*Based on industry and OEM standard engine tests

Features	Advantages and Potential Benefits
Active cleaning agents	Helps to prevent the buildup of harmful deposits to enable long and clean engine life** Provides outstanding engine cleanliness and sludge control
Outstanding high-temperature thermal and oxidation stability	Helps to reduce oil aging for protection throughout your oil drain interval
Enhanced frictional properties	Provides fuel economy improvement versus Mobil 1 ESP Formula 5W-30
Excellent low temperature capabilities	Quick cold weather performance to help provide protection at start-up
Wear protection	Provides outstanding wear protection**

### Applications

Mobil 1 ESP X3 0W-40 is recommended for high-performance engines requiring GPFs (gasoline particulate filters).

- Mobil 1 ESP X3 0W-40 can only be used in the vehicles for which it is approved. It is not backward compatible with vehicle engines requiring an A40, C30 or C20. \*\*\*

\*\*\* Always consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and specifications

### Specifications and Approvals

<b>This product has the following approvals:</b>
PORSCHE C40
MB 229.31

**This product has the following approvals:**

MB 229.51

MB 229.52

GM dexos2

VW 511 00

**This product meets or exceeds the requirements of:**

ACEA C3

FIAT FIAT 9.55535-S2

API SN Engine Test Requirements

API SN PLUS

**Properties and Specifications**

Property	
Grade	SAE 0W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.846
Flash Point, Cleveland Open Cup, °C, ASTM D92	230
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.8
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.1
Pour Point, °C, ASTM D97	-48
Viscosity Index, ASTM D2270	204

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

ExxonMobil Lubricants and Specialties Europe division of ExxonMobil Petroleum & Chemical BV

Polderdijkweg

B-2030 Antwerpen

Automotive products: 0800 80634

Industrial products: 0800 80635

Fax: 0800 80648

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

[www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved