



Mobil Super™ 2000 X1 15W-40

Mobil Passenger Vehicle Lube , Brazil

Semi-synthetic premium oil for passenger vehicles

Product Description

Mobil Super™ 2000 X1 15W-40 is a semi-synthetic oil that provides long engine life and protection against sludge and wear.

Features and Benefits

Mobil Super 2000 products are fully industry proven so you can be confident that you will get the performance you want from your vehicle. Mobil Super 2000 X1 15W-40 provides:

- Better prevention of sludge formation
- Excellent engine cleanliness
- Excellent protection at high temperatures
- Excellent wear protection
- Good performance in cold starts

Applications

Mobil Super 2000 products are formulated to give you confidence that your engine is receiving protection that goes far beyond what conventional oils can provide. ExxonMobil recommends the Mobil Super™ 2000 X1 15W-40 if you occasionally experience demanding driving conditions:

- Gasoline engines
- Passenger cars, sports trucks, light trucks, and vans
- Highway cruising driving and stop-start driving in the city
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

API SM

This product meets or exceeds the requirements of:

API SN

Properties and Specifications

Property	
Grade	SAE 15W-40
Appearance, AMS 1738	Clear and Bright
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Pour Point, °C, ASTM D97	-32
Viscosity Index, ASTM D2270	136
Total Base Number, mgKOH/g, ASTM D2896	7.4
Density @ 15.6 C, g/ml, ASTM D4052	0.8739

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Esso Brasileira de Petróleo Ltda.

Rua Victor Civita, 77, Bloco 1

22775-044 Rio de Janeiro-RJ-BRASIL

5521 3433-2000

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved