



## Mobil Pegasus Compressor Oil 264 and 460

Mobil Industrial , Canada

Premium Quality Lubricants for Reciprocating Natural Gas Compressors

### Product Description

The Mobil Pegasus Compressor Oils 264 & 460 have been specifically formulated from highly refined paraffinic base oils and high performance additives to provide excellent performance in reciprocating natural gas compressors. Both ISO viscosity grades are formulated for outstanding cylinder and piston ring lubrication, excellent oxidation resistance, and excellent chemical tolerance.

### Features and Benefits

Both the 264 and 460 grades, when used within their appropriate recommended application temperature and viscosity range, offer the following features and benefits:

- Outstanding cylinder and piston ring lubrication
- The unique combination of additives protects against separation of dispersion-type additives in lubricator reservoirs, as well as downstream separators and chillers.
- High temperature stability and excellent oxidation resistance contribute to low sludge and deposit formation.
- Chemical tolerance - Mobil Pegasus Compressor Oils 264 and 460 have improved tolerance to contamination by hydrogen sulphide, amines, glycols or other scrubber solutions.
- Reduced sight glass staining of compressors equipped with automatic lubricators.

### Applications

Mobil Pegasus Compressor Oils 264 and 460, for natural gas service, are ideal for initial break-in of compressor cylinders and packings. Their use should continue for 300-500 hours while the lubricated components attain a high polish. Thereafter, their use may be discontinued in "sweet" and "dry" gas service if a lower viscosity is acceptable to the compressor manufacturer.

If the gas being compressed is sour, wet, or contaminated with scrubber solution, Mobil Pegasus Compressor Oils 264 or 460 should continue to be used rather than an engine oil type lubricant. In this way, dilution by condensates can be tolerated while a satisfactory viscosity is maintained.

Because of the high viscosity of these two grades, ample warm up time must be provided to heat the oil enough facilitate pumping from storage containers to lubricator reservoirs.

### Typical Properties

Grade	264	460
Kinematic Viscosity		
cSt @ 40 °C	280	485
cSt @ 100 °C	23	35
Pour Point °C	-12	-12
Flash Point °C	280	280
Density @ 15 °C	0.894	0.896
Colour ASTM	3	2.5

### Health and Safety

The products described on this data sheet are manufactured from high quality petroleum base stocks, carefully blended with selected additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into the eyes, ingestion or vapour inhalation. Please refer to the Material Safety Data Sheet for further information.

Note: The products described on this data sheet are NOT controlled under Canadian WHMIS legislation.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2020

### Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved