



## Mobil Super™ 3000 Formula V 0W40

Mobil Passenger Vehicle Lube , 中国

Premium Fully Synthetic Passenger Vehicle Engine Oil

### Product Description

MOBIL SUPER 3000 FORMULA V 0W-40 is ultra premium synthetic engine oils, designed to provide outstanding levels of protection and performance.

### Features and Benefits

MOBIL SUPER 3000 FORMULA V 0W-40 is industry proven so you can trust you will get the performance you want from your vehicle.

MOBIL SUPER 3000 FORMULA V 0W-40 provides:

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

### Applications

MOBIL SUPER 3000 FORMULA V 0W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend MOBIL SUPER 3000 FORMULA V 0W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- Turbo-Chargers and Direct Injection engines
- High Performance Engines

### Specifications and Approvals

**This product has the following builder approvals:**

VW 502 00

VW 505 00

**This product meets or exceeds the requirements of:**

ACEA A3/B3

ACEA A3/B4-12

This product meets or exceeds the requirements of:

API SN

### Properties and Specifications

Property	
Grade	SAE 0W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.3
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	78.52
Ash, Sulfated, mass%, ASTM D874	1.15
Phosphorus, mass%, ASTM D4951	0.095
Flash Point, °C, ASTM D92	224
Density @ 60 F, kg/m <sup>3</sup> , ASTM D4052	0.8433
Pour Point, °C, ASTM D97	-39

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon

Mobil

Esso

XTO

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved