



Mobil Super 2000 X1 10W-40

Mobil Passenger Vehicle Lube , Colombia

Premium Semi-Synthetic Passenger Vehicle Motor Oil

Product Description

Mobil Super™ 2000 X1 10W-40 is a semi-synthetic motor oil that provides long engine life and protection against sludge & wear.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 X1 10W-40 provides:

- Enhanced sludge prevention
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent wear protection
- Good cold start-up performance

Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. ExxonMobil recommends Mobil Super™ 2000 X1 10W-40 if you occasionally experience demanding driving conditions:

- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:
AVTOVAZ (LADA cars)
MB-Approval 229.1
VW 501 01
VW 505 00

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
AAE (STO 003) Group B7
API SJ
API SL
API SM
API SN
API SN PLUS
ACEA A3/B3

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.2
Density @ 15.6 C, g/ml, ASTM D4052	0.8669
Viscosity Index, ASTM D2270	155
Pour Point, °C, ASTM D97	-33
Flash Point, Cleveland Open Cup, °C, ASTM D92	234
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	94.6

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved