



## Mobil Screenwash Concentrate -65°C

Mobil Ancillary , Germany

### Product Description

Highly concentrated Screenwash Concentrate that protects down to -65°C.

### Features and Benefits

Suitable for the most severe winter conditions.

Helps to prevent windscreen washer freeze-up.

Added fragrance.

Can also be used all year round to remove dirt & grime from windscreens.

### Applications

Pour into your screenwash reservoir and dilute with water as required.

| Screenwash       | Water          | Freeze protection     |
|------------------|----------------|-----------------------|
| 10% 25% 50% 100% | 90% 75% 50% 0% | -2°C -9°C -25°C -65°C |

### Typical Properties

|                                     |                           |
|-------------------------------------|---------------------------|
| Mobil Screenwash concentrate -65°C. |                           |
| Color / Odour                       | Clear Blue Liquid / Apple |
| Density at 20°C, g/cm <sup>3</sup>  | 0.91 g/cm <sup>3</sup>    |

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office or via the Internet, or provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Mobil , Mobil 1 and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.com/de/de-de/kontakt>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

Exxon

Mobil

Esso

XTOL

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved