



Wyrol HS
Mobil Industrial , Denmark
Hydraulic Oil

Product Description

Wyrol HS oils are premium synthetic, low staining, low gum-forming, anti-wear hydraulic fluids that are specifically designed for use in modern aluminium rolling mills. They are designed to meet the most up-to-date requirements of high productivity aluminium cold rolling mills. Leakage of conventional hydraulic fluids leads to contamination of the aluminium rolling oil system; this may cause staining and gum formation on finished metal surfaces. However, contamination of the rolling mill by Wyrol HS significantly reduces this effect. Wyrol HS has good anti-wear properties, excellent oxidation stability and good protection against rust and corrosion. Although Wyrol HS is a synthetic product, it is miscible with mineral oil, so change over from conventional hydraulic oil to Wyrol HS can be achieved with relative ease. Due to the nature of the base oil, Wyrol HS does not meet U.S. FDA Regulation 21 CFR 178.3910(a). If this is required, Wyrol H should be used.

Features and Benefits

Wyrol HS are high performance synthetic hydraulic fluids, which exhibit very low staining characteristics reducing the potential of production material rejects. Excellent oxidation stability and good anti-wear protection properties result in longer oil life and improved hydraulic component performance.

Wyrol HS oils offer the following benefits:

- Low staining characteristics reduce the potential of production rejects
- Good anti-wear properties reduce hydraulic system component wear and extend service life
- Excellent oxidation stability minimises system deposits and improves oil life, reducing maintenance costs

Applications

- Hydraulic systems in aluminium cold rolling mills
- Suitable for use in low and high pressure hydraulic systems
- Recommended for gear, vane and piston pumps in hydraulic applications

Typical Properties

Wyrol HS	22	46
Density at 15 °C, kg/m3, ASTM D 4052	868	870
Kinematic Viscosity at 40°C, mm2/s, ISO 3104	22	44
Kinematic Viscosity at 100 °C, mm2/s, ISO 3104	3.7	5.3
Pour Point, °C, ISO 3016	-51	-42
Flash Point, COC, °C, ISO 2592	160	175
Copper Corrosion, 3h, 100°C, rating, ISO 2160	1	1
Rust Prevention, distilled water, ISO 7120	Pass	Pass

Health and Safety


Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

ExxonMobil Nordic
Affiliate of ExxonMobil Nordic AS, Norway
Gydevang 39-41
DK-3450 Alleroed, Denmark
Tel: +45 45 99 02 10
Fax : +45 45 99 02 80
www.exxonmobil.no

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved