



Mobil Pegasus 705

Mobil Industrial , Egypt

Gas Engine Oil

Product Description

Mobil Pegasus 705 is a high performance mineral gas engine oil formulated to lubricate a wide range of natural gas-fuelled engines, including lean-burn, high-designs sensitive to valve recession. Mobil Pegasus 705 is an SAE 40 intermediate ash product that meets the new lubrication requirements of the severe, turbo-charger, higher-speed, four-cycle gas engines. Mobil Pegasus 705 is suitable for engines with low levels of hydrogen sulfide in the fuel.

Features and Benefits

- Excellent protection for valve guide faces and seats
- Maximum protection against piston scuffing, scoring, and cylinder liner wear
- Improved engine cleanliness
- Excellent resistance to oxidation and nitration
- Minimum ash deposits in lean-burn and low-oil consumption gas engines
- Excellent resistance to foaming, excellent TBN retention and corrosion resistance

Applications

Mobil Pegasus 705 is recommended to be used in both medium- and high-speed gas engines.

Specifications and Approvals

Mobil Pegasus 705 meets or exceeds the requirements of:	
Caterpillar	X

Mobil Pegasus 705 has the following builder approvals:	
MTU Category 1	X
PERKINS GAS ENGINE OIL - NATURAL GAS	X
GE JENBACHER TI 1000-1107	X
MWN GmbH TR 0199-99-2105/7, Lube Oils for Gas Engines	X
WARTSILA 34SG	X
WARTSILA 32 DF	X
WARTSILA 28SG	X
WARTSILA 220 SG	X
WARTSILA NSD W25SG	X
WARTSILA NSD W12V150SG, W12V175SG, W16V175SG	X
MAN approval 3271-2	X

Typical Properties

Mobil Pegasus 705	Test Method	Unit	
CMCS Code			97F517

Mobil Pegasus 705	Test Method	Unit	
Appearance	Visual		Bright and Clear
Viscosity @			
40°C	ASTM D 445	cSt	126.2
100°C	ASTM D 445	cSt	13.2
Viscosity Index	ASTM D 2270	none	98
Flash Point COC	ASTM D 92	°C	252
Pour Point	ASTM D 97	°C	-18
Total Base Number	ASTM D 2896	mg KOH/g	5.6
Sulfated Ash	ASTM D 874	wt%	0.5
Calcium	ASTM D 4951	wt%	0.12
Zinc	ASTM D 4951	wt%	0.032
Foam Seq I, Tend/Stab	ASTM D 892	ml/ml	5/0
Foam Seq II, Tend/Stab	ASTM D 892	ml/ml	40/0

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommend provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This p should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Pegasus 705 are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

01-2020
ExxonMobil Egypt (S.A.E.)
1097 Cornish El-Nil, Garden City, Cairo, Egypt

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.global.mobil.com/en/contact-us>
+ 20 2 795 4850/60
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTON

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved