



Mobilfluid 428

Mobil Commercial Vehicle Lube , United Kingdom

Modern extra high performance multipurpose tractor oil (UTTO)

Product Description

Mobilfluid 428 is a modern extra high performance multipurpose tractor lubricant engineered to meet or exceed the requirements of most equipment builders for hydraulic and transmission compartments. It is designed to optimize the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. Mobilfluid 428 is recommended to be used in off-highway industries including: agriculture, construction, and quarrying. Its friction characteristics helps reduce wet brake and Power Take-Off (PTO) chatter. This next generation product is formulated from high quality base oils and advanced additive technology to deliver excellent thermal stability combined with high shear stability for an SAE 10W-30 viscosity grade. Based on the excellent shear stability and air handling, Mobilfluid 428 is suitable for use in conventional CVTs (hydraulic pump plus planetary gear componentry).

Features and Benefits

Next generation technology has vastly improved the performance capabilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative powertrain designs. These designs have changed and increased the requirements of powertrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. Mobilfluid 428 delivers exceptional performance in today's powertrain transmissions, drive axles, clutches, PTOs and hydraulic systems. The key benefits include:

Features	Advantages and Potential Benefits
Excellent frictional properties	Optimal clutch and PTO performance
Compatible with clutch materials and elastomers	Long clutch life and reduced leakage
High viscosity index and improved shear stability	Consistent operating response
Excellent protection against rust, corrosion, and yellow metal etching	Protects equipment in wet or humid environments and prevents premature wear
Enhanced low temperature properties	Responsive operation and effective lubrication in cold weather applications
Strong anti-wear and extreme pressure properties	Reduces wear, extends equipment life, and reduces maintenance costs
Excellent thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant
Multipurpose capability	Simplifies inventory and reduces misapplication problems
Good filterability	Keeps systems clean and operating smoothly

Applications

- Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives
- Recommended in off-highway industries including: agriculture, construction, and quarrying
- Recommended for top-up and refill of systems
- Do not use in passenger car automatic transmissions
- Recommended by ExxonMobil for use in applications requiring API GL-4 lubricants in all gear applications except hypoid gear designs

This product is recommended for use in applications requiring:

AGCO Powerfluid 821 XL
 Allison C-4
 API GI-4
 ASTM D6973 (Eaton 35VQ) vane pump test
 Case New Holland MAT 3505 / MAT 3525 / MAT 3540
 Case IH MS 1204 / 1205 / 1206 / 1207 / 1209
 Caterpillar TO-2
 Denison UTTO-THF / HF-0 / HF-1 / HF-2
 Ford M2C86-B / M2C134-D
 Ford New Holland FNHA-2-C-201.00
 John Deere J20C
 Kubota UDT / Super UDT 2
 Massey Ferguson M-1135 / M-114 / M-1143 / M-1145
 New Holland WB NWH 410B
 Volvo WB-101
 ZF TE-ML 03E / 05F / 06K / 17E / 21 F

Specifications and Approvals

This product has the following approvals:
VOLVO WB-101

This product is recommended for use in applications requiring:
AGCO Powerfluid 821 XL
Allison C-4
API GL-4
CNH MAT 3505
CNH MAT 3525
CNH MAT 3540
Denison HF-0
Denison HF-1
Denison HF-2
FORDNH FNHA-2-C-201.00
Ford ESEN-M2C86-B
FORD ESN-M2C134-D
JICASE MS 1204
JICASE MS 1205
JICASE MS 1206

This product is recommended for use in applications requiring:

JICASE MS 1207

JICASE MS 1209

MASSEY FERGUSON CMS M1145

MASSEY FERGUSON CMS M1143

MASSEY FERGUSON CMS M1141

MASSEY FERGUSON CMS M1135

New Holland WB NWH 410B

ZF TE-ML 03E

ZF TE-ML 05F

ZF TE-ML 06K

ZF TE-ML 17E

ZF TE-ML 21F

Denison UTTO/THF

G2-08

RENAULT AGRICULTURE (M1145)

GEAR OIL HP

KUBOTA SUPER UDT 2

KUBOTA UDT

This product meets or exceeds the requirements of:

ASTM D6973 (Eaton 35VQ) vane pump test

JOHN DEERE JDM J20C

Properties and Specifications

Property	
Grade	SAE 10W-30
Density @ 15 C, g/ml, ASTM D4052	0.866
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	59
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.3

Property	
Viscosity Index, ASTM D2270	141
Flash Point, °C, ASTM D92	243
Pour Point, °C, ASTM D97	-48

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.co.uk/en-gb/contact-us-technical>

44 (0)1372 222000


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved