



Mobil SHC™ PM Series

Mobil Industrial , Ireland

Paper Machine Lubricants

Product Description

Mobil SHC™ PM Series products are superior performance synthetic lubricants specifically designed for the most demanding industrial paper machine circuits. The Mobil SHC PM Series oils are formulated to provide outstanding protection of gears and bearings operating under the most severe conditions. The very low pour points and a naturally high viscosity index (VI) which helps ensure good low temperature start-up while maintaining excellent viscosity characteristics at very high temperatures. The fluids are very shear stable and maintain viscosity control even when subjected to severe mechanical shear in heavily loaded bearing gears. Their low traction coefficient and high viscosity index can help result in lower energy consumption and reduced component operating temperatures.

To develop the latest Mobil SHC technology for Mobil SHC PM Series oils, ExxonMobil product formulation scientists chose select base oils because of their excellent thermal/oxidative resistance potential and combined them with a balanced additive system, which complement the inherent benefits of the base oils to attain performance standards. These fluids permit the use of higher steam pressures, temperatures and machine speeds common in high output paper machines and can rolls. Their outstanding hydrolytic stability and filterability assure excellent performance in the presence of water and the ability to retain effective filtration even at fine filtration levels. They readily separate water and retain their colour characteristics for extended periods of operation under severe conditions.

Features and Benefits

The Mobil SHC PM Series oils represent a technological advance in paper machine lubrication. Their excellent performance capabilities in the areas of wear protection, enhanced oxidation stability, chemical stability, effective rust and corrosion protection, colour stability, and filterability not only prolong maintenance service intervals but can improve machine performance and increase production capacity. This can result in less required maintenance and longer equipment life.

| Features | Advantages and Potential Benefits |
|---|---|
| Excellent Wide Temperature Performance | Easier start-up and improved lubrication at cold starts Extra margin of protection at elevated temperatures Better control of feed rates |
| Exceptional Wear Protection | Improved bearing and gear performance |
| Outstanding Oxidation and Thermal Stability | Longer oil life Lower filter replacement costs Cleaner systems Reduction of system deposits |
| Effective Water Separation Properties | Allows easier removal of water Reduces formation of undesirable emulsions in systems |
| Low Traction Coefficient | Reduced energy consumption Lower operating temperatures Reduced wear |
| Excellent Filterability | Keeps oil lines and flow control mechanisms free of deposits Improved oil flow and cooling performance Lowers filter replacement costs |
| High Level Rust and Corrosion Protection | Protects gears and bearings in wet environments Provides vapour space protection for areas of bearing and gear cavities above normally wetted surfaces |

Applications

- Lubrication of severe industrial paper machine circulating systems
- Application involving circulation systems operating over a wide temperature range such as calendar rolls
- Systems that must be started and brought on line quickly
- Circulation systems lubricating gears and bearings

Properties and Specifications

| Property | 150 | 220 | 320 | 460 |
|---|---------|---------|---------|---------|
| Grade | ISO 150 | ISO 220 | ISO 320 | ISO 460 |
| Copper Strip Corrosion, 24 h, 100 C, Rating, ASTM D130 | 1B | 1B | 1B | 1B |
| Density @ 15 C, kg/l, ASTM D1298 | 0.857 | | | |
| Emulsion, Time to 40/40/0, 82 C, min, ASTM D1401 | 15 | 25 | 30 | 30 |
| FZG 4-Square Load Support, Fail Stage, DIN 51354 | 11 | | | |
| FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1 | | 11 | 11 | 11 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 220 | 220 | 220 | 220 |
| Hydrolytic Stability, Acid Number Change, mgKOH/g, ASTM D2619 | | 0 | 0 | 0 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 18.9 | 25.6 | 34.7 | 44.8 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 158 | 225 | 325 | 465 |
| Pour Point, °C, ASTM D97 | -39 | -36 | -33 | -27 |
| Rust Characteristics, Procedure B, ASTM D665 | PASS | PASS | PASS | PASS |
| Specific Gravity, 15 C/15 C, ASTM D1298 | | 0.863 | 0.865 | 0.874 |
| Viscosity Index, ASTM D2270 | 124 | 127 | 130 | 137 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Esso Petroleum Company limited

ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved