



## Mobil Delvac Legend™ 15W-40 City Logistics™

Mobil Commercial Vehicle Lube , India

High Performance Light Duty Diesel Engine Oil

### Product Description

Mobil Delvac Legend™ 15W-40 City Logistics™ is a high performance diesel engine oil that provides protection of diesel engines operating in intra-city and inter-city logistics applications. It is suitable for use in Small and Light duty vehicle, involving frequent start-stop service, variable loads & higher idle times.

Mobil Delvac Legend™ 15W-40 City Logistics™ is recommended by ExxonMobil for use in a wide range of modern & new light-duty commercial vehicles across multiple applications for e.g. Mini Trucks, Cargo vans, Pick-ups, Food & Service Vans, etc.

### Features and Benefits

Mobil Delvac Legend™ 15W-40 City Logistics™ delivers excellent performance in both modern light commercial vehicles as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge and deposits, thereby keeping internal engine parts clean
TBN reserve	Controls Deposit and helps acid neutralisation due to Start-Stop service
Stay-in-grade shear stability	Wear protection and reduced oil consumption
Excellent detergency/dispersancy	Clean engines and long engine life

### Applications

Mobil Delvac Legend™ 15W-40 City Logistics™ is recommended for use in applications that cover small & light commercial vehicles like Mini Trucks, Cargo vans, Pick-ups, Food & Service Vans, etc.

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
API CH-4

### Properties and Specifications

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	137
Total Base Number, mgKOH/g, ASTM D2896	8

Property	
Pour Point, °C, ASTM D97	-33
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	116
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	15.2
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Density @ 15 C, kg/l, ASTM D4052	0.869
Ash, Sulfated, mass%, ASTM D874	1.1

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003–2019 Exxon Mobil Corporation. All Rights Reserved