



Mobil Delvac long life grease

Mobil Grease , India  
Lithium Automotive Grease

Product Description

Mobil Delvac long life grease is a high quality, multipurpose, NLGI 3 grade, lithium grease based on an ISO VG 160 mineral oil. It is formulated to provide added protection against rusting and water washout in general purpose automotive applications at moderate temperatures and loads.

Features and Benefits

Mobil Delvac long life grease is suitable for general purpose automotive applications and provides the following benefits:

- Wide operating temperature range
- Good resistance to water washout
- Extra protection against rust and corrosion
- Excellent structural stability
- Lead, chlorine and nitrite free

Applications

Mobil Delvac long life grease is recommended for the lubrication of automotive chassis components, wheel bearings, clutch bearings, universal joints and ball joints steering and suspension systems of passenger cars, trucks, farm tractors and most other types of mobile equipment operating under moderate conditions. The recommended operating temperature range of Mobil Delvac long life grease is -20 Deg C to 120 Deg C. In applications where heavy or shock loading is a factor, extreme pressure greases are preferred.

Typical Properties

Mobil Delvac long life grease	Test Method	Unit	
NLGI Grade			3
Soap Type			Lithium
Color	Visual		Red
Structure	Visual		Smooth
Penetration, Worked	ASTM D217	0.1 mm	235
Dropping Point	ASTM D2265	Deg C	180
Viscosity of Oil @ 40 Deg C	ASTM D445	cSt	160

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil Services & Technology Private Limited

(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,

Whitefield Main Road, Bangalore – 560048, Karnataka, India

+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved