



Mobil Super™ 2000 5W-30

Mobil Passenger Vehicle Lube , Japan

Synthetic Technology Engine Oil

Product Description

Mobil Super™ 2000 5W-30 is a high-performance synthetic blend oil that has excellent low friction properties and complies with the latest fuel efficiency standard ILSAC GF-6A.

Features and Benefits

- Outstanding anti-wear protection for vehicles of all ages against tough conditions in city driving.
- Outstanding protection against harmful deposits to maintain engine cleanliness.
- Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures

Applications

Suitable for fuel economy cars

Specifications and Approvals

This product meets or exceeds the requirements of:

API SP

ILSAC GF-6A

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	151
Total Base Number, mgKOH/g, ASTM D2896	7.5
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	228
Ash, Sulfated, mass%, ASTM D874	0.8
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	16400
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	63

Property	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Density @ 15.6 C, g/ml, ASTM D4052	0.859

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

EMG Lubricants Godo Kaisha

Lubricants Customer Response Center

Yokohama Blue Avenue, 4-4-2 Minatomirai, Nishi-Ku, Yokohama-city

Kanagawa 220-0012

Japan

Tel : 0120-016-313 (only from Japan local)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved