



Mobil Diesel DL1 5W30

Mobil Passenger Vehicle Lube , Japan

Premium Semi-Synthetic Passenger Diesel Engine Oil

Product Description

Mobil™ Diesel DL-1 5W-30 is a high performance semi-synthetic premium engine oil that is formulated for diesel powered vehicles, providing excellent performance and protection.

Features and Benefits

Mobil Diesel DL-1 5W-30 is designed to protect against the damage resulting from contamination and heat experience in tough driving conditions.

Mobil Diesel DL-1 5W-30 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection

Applications

Mobil Diesel DL-1 5W-30 is formulated to give you confidence of protection beyond that of conventional oils. This product is suitable for use in all diesel-powered vehicles.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	9.6
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	54
Viscosity Index, ASTM D2270	164
Ash, Sulfated, mass%, ASTM D874	0.5
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	3.0
Pour Point, °C, ASTM D97	-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	224
Density @ 15 C, g/cm ³ , ASTM D4052	0.860

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims>

[/psims.aspx](#)

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

EMG Lubricants Godo Kaisha

Lubricants Customer Response Center

Yokohama Blue Avenue, 4-4-2 Minatomirai, Nishi-Ku, Yokohama-city

Kanagawa 220-0012

Japan

Tel : 0120-016-313 (only from Japan local)

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved