



Mobil DTE™ 20 ZF Series

Mobil Industrial , Sri Lanka

Hydraulic Oil

Product Description

Mobil DTE™ 20 ZF Series oils are superior hydraulic oils specifically designed to meet the needs of modern, high pressure, industrial and mobile equipment hydraulic systems. They are formulated from high quality base stocks and specially selected zinc free additives. This unique additive system was developed to give exceptional protection due to excellent anti-wear performance in severe hydraulic applications.

The Mobil DTE 20 ZF oils exhibit excellent oxidation and thermal stability properties which can help to provide extended oil and filter life, as well as optimum equipment protection, thereby reducing both maintenance and product disposal costs. They are designed to work with systems operating under moderate to severe conditions where high levels of anti-wear and film strength protection are needed.

Features and Benefits

The Mobil DTE 20 ZF Series hydraulic oils exhibit excellent oxidation resistance and thermal stability characteristics that can lead to extension of oil and filter change intervals and help to provide clean systems and trouble-free operation. Their high level of anti-wear properties and excellent film strength characteristics can lead to equipment performance that can not only result in fewer breakdowns, but also can help to enhance productivity. Their outstanding demulsibility permits the oils to work well in systems contaminated with small amounts of water, and readily separate large amounts of water.

Features	Advantages and Potential Benefits
Thermal and Oxidation Stability	Provides long oil and equipment life
Anti-wear Properties	Helps reduce wear and protects pumps and components for extended equipment life
Excellent Demulsibility Characteristics	Protects systems where small quantities of moisture are present
Multi Metal Compatibility	Helps ensure excellent performance and protection with a wide variety of component metallurgy
Meets a Wide Range of Equipment Requirements	Minimizes inventory requirements

Applications

- Systems employing multi-metal designs in pumps and other system components
- Applications where cross-contamination of hydraulic fluids and coolants can occur
- High pressure vane, piston and gear pumps
- Where small amounts of water are unavoidable
- In systems containing gears and bearings
- Systems requiring a high degree of load-carrying capability and anti-wear protection

Specifications and Approvals

This product has the following approvals:	MOBIL DTE 24 ZF	MOBIL DTE 25 ZF	MOBIL DTE 26 ZF	MOBIL DTE 27 ZF
Denison HF-0	X	X	X	

This product has the following approvals:	MOBIL DTE 24 ZF	MOBIL DTE 25 ZF	MOBIL DTE 26 ZF	MOBIL DTE 27 ZF
Denison HF-1	X	X	X	
Denison HF-2	X	X	X	

This product meets or exceeds the requirements of:	MOBIL DTE 24 ZF	MOBIL DTE 25 ZF	MOBIL DTE 26 ZF	MOBIL DTE 27 ZF
DIN 51524-2:2017-06	X	X	X	X
ISO L-HM (ISO 11158:2009)	X	X	X	X

Properties and Specifications

Property	MOBIL DTE 24 ZF	MOBIL DTE 25 ZF	MOBIL DTE 26 ZF	MOBIL DTE 27 ZF
Grade	ISO 32	ISO 46	ISO 68	ISO 100
Density @ 15 C, kg/l, ASTM D4052	0.8548	0.8635	0.8723	0.8801
Flash Point, Cleveland Open Cup, °C, ASTM D92	235	237	242	250
Foam, Sequence I, Stability, ml, ASTM D892	0	0	0	0
Foam, Sequence I, Tendency, ml, ASTM D892	10	10	10	10
Foam, Sequence II, Stability, ml, ASTM D892	0	0	0	0
Foam, Sequence II, Tendency, ml, ASTM D892	10	10	10	10
Foam, Sequence III, Stability, ml, ASTM D892	0	0	0	0
Foam, Sequence III, Tendency, ml, ASTM D892	10	10	10	10
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	5.63	7.02	8.90	11.27
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	32.15	46	67.88	99.77
Pour Point, °C, ASTM D97	-39	-36	-33	-33
Rust Prevention, 24 h, ASTM D665-PROB	PASS	PASS	PASS	PASS
Viscosity Index, ASTM D2270	114	110	104	99

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved