



Mobil SHC Gear 1500, 3200 and 6800

Mobil Industrial , North Macedonia

Gear Oils

Product Description

The Mobil SHC Gear 1500, 3200, and 6800 lubricants are supreme performance heavy-duty gear oils primarily designed for all kinds of enclosed gearing as well as plain and rolling element bearings. They are designed to provide outstanding service in terms of equipment protection, oil life, and problem-free operation enabling increased customer productivity. These scientifically engineered synthetic lubricants are formulated from synthetic base fluids that have exceptional oxidation and thermal stability properties and excellent low temperature fluidity. The combination of a naturally high viscosity index and a unique additive system enables these products to provide outstanding performance under severe high and low temperature operating conditions. The nature of the synthetic base fluids also contributes to the products' excellent low temperature performance. They have excellent protection against gear scuffing and resistance to shock loading. The synthetic base stocks have inherent traction properties that result in low fluid friction in the load zone of non-conforming surfaces such as gears and rolling element bearings. Reduced fluid friction provides for lower operating temperatures and improved gear efficiency.

The Mobil SHC Gear 1500, 3200, and 6800 find application in a wide range of enclosed gear applications, as well as plain and rolling element bearings. Because of their very high viscosities they can meet the lubrication needs of very slow speed and high load/high temperature gears and bearings; they are ideal for situations in which conventional products operate in the boundary regime. There may be situations where a lubricant bath or recirculation system is used to apply the oil.

Mobil SHC Gear 1500, 3200, and 6800 are the products of choice for many OEMs and customers world-wide based on their wide application range and superior performance in tough situations.

Features and Benefits

The Mobil SHC Gear 1500, 3200, and 6800 are leading members of the Mobil SHC brand of products that are world-renowned for their innovation and performance. These scientifically engineered synthetic lubricants symbolize the continuing commitment to using advanced technology to provide outstanding lubricant products. Mobil SHC Gear 1500, 3200, and 6800 lubricants provide benefits not possible with mineral stocks, particularly under extreme high and low temperature operating conditions, and deliver performance features and customer benefits.

Our formulation scientists have used a proprietary additive combination that fortifies the base fluids to provide excellent gear scuffing protection and anti-wear performance, even in shock load situations. The resulting finished products have shown exceptional performance in OEM evaluations, customer field tests, and commercial use. These high viscosity grades are particularly effective in low-speed, high load, high temperature situations and provide excellent gear and bearing protection, longer oil life and excellent all-round service compared with conventional products.

Specific features and potential benefits for the Mobil SHC Gear 1500, 3200, and 6800 lubricants include:

Features	Advantages and Potential Benefits
Outstanding load-carrying and antiwear properties	Helps extended gear life and reduce maintenance costs
Very high viscosity grades available, without reduction of properties or performance capability	Provides excellent EHL film protection of gears and bearings even at slow speeds, high loads and high temperatures
	Can be used to convert all-loss systems to circulation
	Can replace grease in some applications resulting in plant product consolidation
High viscosity index	Trouble-free operation over a wide temperature range particularly at extremely low temperatures.
Low traction properties	Can help improved gear efficiency and lower operating temperatures lead to lower operating costs

Features	Advantages and Potential Benefits
Outstanding thermal/oxidation resistance and long product life	Helps reduce lubricant consumption, helps reduce product and change-out costs
Light color	Helps avoid need for gear cleaning prior to inspections, helping to reduce maintenance costs

### Applications

Application Considerations: While the Mobil SHC Gear 1500, 3200, and 6800 are compatible with mineral oil based products, admixture may detract from performance. Consequently it is recommended that before changing a system to one of the Mobil SHC Gear 1500, 3200, or 6800 lubricants, it should be thoroughly cleaned out and flushed to achieve the maximum performance benefits.

Mobil SHC Gear 1500, 3200, and 6800 oils are recommended for all types of enclosed steel-on-steel gear drives. They are suitable for both circulation and lubrication systems. They are particularly recommended for gear sets operating under heavy or shock loads and low speeds where boundary lubrication may occur. Applications for this product family are:

- Mobil SHC Gear 1500, 3200 and 6800 - Industrial enclosed spur, helical and bevel gears, especially slow speed, and/or high load units.
- Mobil SHC Gear 1500, 3200 and 6800 - Plain and rolling element bearings, especially in slow speed, and/or high load applications.
- Mobil SHC Gear 3200 and 6800 - Railroad DC Traction Motor drives.
- Mobil SHC Gear 3200 and 6800 - Certain open gear applications such as oiling pinions or specially designed circulation systems.

### Properties and Specifications

Property	1500	3200	6800
Grade	ISO 1500	ISO 3200	
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1B	1B	1B
Density @ 15.6 C, kg/l, ASTM D1298	0.88	0.89	0.9
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1(mod)	13+	13+	13+
Flash Point, Cleveland Open Cup, °C, ASTM D92	230	230	230
Foam, Sequence I, Stability, ml, ASTM D892	0	0	0
Foam, Sequence I, Tendency, ml, ASTM D892	0	0	0
Foam, Sequence II, Stability, ml, ASTM D892	0	0	0
Foam, Sequence II, Tendency, ml, ASTM D892	0	0	0
Foam, Sequence III, Stability, ml, ASTM D892	0	0	0
Foam, Sequence III, Tendency, ml, ASTM D892	0	0	0
Four-Ball Extreme Pressure Test, Load Wear Index, kgf, ASTM D2783	48	48	48
Four-Ball Extreme Pressure Test, Weld Load, kgf, ASTM D2783	250	250	250
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	113	183	365
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	1500	3200	8200
Pour Point, °C, ASTM D5950	-18	-9	-6

Property	1500	3200	6800
Rust Characteristics, Procedure B, ASTM D665	PASS	PASS	PASS
Viscosity Index, ASTM D2270	165	165	180

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

MTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved