



## Mobil Super™ 3000 Formula P 5W-30

Mobil Passenger Vehicle Lube , North Macedonia

High Performance Motor Oil

### Product Description

Mobil Super 3000 Formula P 5W-30 is a low ash high performance motor oil designed to help prolong the life and maintain the efficiency of the car exhaust Emission Reduction Systems in both diesel and gasoline powered automobiles.

### Features and Benefits

Mobil Super 3000 Formula P 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Low Ash, low phosphorous and low sulfur formulation helping to prolong the life and maintain the efficiency of the Emission Reduction Systems in both Diesel and Gasoline powered engines.
- Fully compatible with most Diesel Particulate Filters and Catalytic Convertors.
- Help achieve fuel economy (as per ACEA C2).
- Excellent low temperature capabilities for reliable cold weather starting allowing fast engine and electrical system protection.
- High performance wear-protection.
- Active cleaning agents reducing deposits and sludge build-up to enable long and clean engine life.

### Applications

Mobil Super 3000 Formula P 5W-30 is recommended for a variety of modern automotive engines, especially the high-performance gasoline, turbo-diesel injection with common rail and other diesel engines, found in the latest passenger cars, SUV's and light vans.

Not recommended for 2-cycle or aviation engines, unless specifically approved by the manufacturer.

### Specifications and Approvals

**This product has the following builder approvals:**

Peugeot/Citroën Automobiles B71 2290

**This product meets or exceeds the requirements of:**

API SN

ACEA C2

### Properties and Specifications

| Property |           |
|----------|-----------|
| Grade    | SAE 5W-30 |

| Property   |      |
|--|------|
| Density @ 15 C, g/ml, ASTM D4052                           | 0.85 |
| Flash Point, °C, ASTM D92                                  | 226  |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 10.5 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 60   |
| Phosphorus, mass%, ASTM D4951                              | 0.08 |
| Pour Point, °C, ASTM D97                                   | -39  |
| Ash, Sulfated, mass%, ASTM D874                            | 0.7  |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.


11-2020

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved