



Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube , Myanmar

High Performance Motor Oil

Product Description

Mobil Special™ 20W-50 is a high performance motor oil for all types of vehicles. Mobil Special 20W-50 delivers engine protection and cleanliness. Mobil Special 20W-50 is recommended for use in a wide range of applications and operating conditions.

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Specifications and Approvals

This product meets or exceeds the requirements of:

API SL

Properties and Specifications

Property	
Grade	SAE 20W-50
Total Base Number, mgKOH/g, ASTM D2896	5.5
Viscosity Index, ASTM D2270	130
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	5.2
Pour Point, °C, ASTM D97	-3
Density @ 15 C, g/ml, ASTM D4052	0.878
Flash Point, °C, ASTM D92	230
Ash, Sulfated, mass%, ASTM D874	0.8
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	185
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	20.5
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	25300

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved