



Mobil Delvac™ 1 Final Drive and Axle Oil

Mobil Commercial Vehicle Lube , Mexico

Product Description

Mobil Delvac™ 1 Final Drive and Axle Oil is an extra high performance drivetrain lubricant that meets the requirements of the Caterpillar FD-1 standard. It is specifically engineered to provide optimum component life when used as recommended in off-highway truck and bulldozer final drives, axles, bevel gears, and differentials, especially those operating under high loads and extreme temperatures. It is formulated from advanced synthetic base oils and the latest additive technology to enable extended oil drain intervals and prolong the life of bearings and gears. The synthetic base oil composition enables excellent performance in some of the harshest operating conditions and over a wide temperature range, in high temperatures as well as temperatures down to -35c.

Features and Benefits

Today's technology has vastly improved the performance capabilities of heavy-duty off-highway equipment innovative drivetrain designs. Additionally, increasing demands for higher productivity and more severe operating conditions put severe stress on axles and final drive components. For optimum durability and performance, Mobil Delvac 1 Final Drive and Axle Oil can be relied on to maintain productivity and minimize maintenance costs.

| Features | Advantages and Potential Benefits |
|--------------------------------------------------------|----------------------------------------------------------------------------------|
| Excellent load carrying, anti-wear, and EP performance | Helps extend component life and reduce cost of operation |
| Optimized thermal and oxidation protection | Long oil life, extended drain and service intervals, and extended component life |
| Exceptional shear stability | Helps minimize wear during severe operation |
| Outstanding low-temperature fluidity | Helps reduce wear during cold temperatures |
| Extended drain and service interval capability | Helps provide lower operating costs and higher productivity |

Applications

Mobil Delvac 1 Final Drive and Axle Oil is recommended for use in off-highway truck and bulldozer front wheels, differentials and final drives requiring CAT FD-1 lubricants. Note that Mobil Delvac 1 Final Drive and Axle Oil should not be used in compartments that contain frictional materials unless an oil meeting the FD-1 specification has been specified.

Specifications and Approvals

| |
|-----------------------------------------------------------|
| This product meets or exceeds the requirements of: |
| Caterpillar FD-1 |

Properties and Specifications

| Property | |
|------------------------------------------------------------|------|
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 320 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 31.6 |

| Property | |
|-----------------------------------------------|--------|
| Viscosity Index, ASTM D2270 | 138 |
| Pour Point, °C, ASTM D97 | -45 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 246 |
| Density @ 15.6 C, kg/l, ASTM D4052 | 0.8573 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved