



## Mobil Delvac XHP Ultra LE SCA 5W-30

Mobil Commercial Vehicle Lube , Netherlands

Advanced Engine and Emission System Protection

### Product Description

Mobil Delvac XHP Ultra LE SCA 5W-30 is an extra high performance synthetic diesel engine oil engineered to provide outstanding protection and fuel economy potential in modern, high performance, low emissions engines used in severe on-highway applications.

This engine oil is specifically designed to meet the Scania LDF-4 specification. Besides fulfilling the latest Scania specification, it can be used when ACEA E6 or E7 is requested.

This engine oil is formulated with advanced synthetic technology base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control and contribute to fuel economy improvement potential. The advanced additive system has been expertly engineered to help prolong the life and maintain the efficiency of emission reduction systems such as the Diesel Particulate Filter (DPF). The DPF is widely used by most builders to comply with emission regulations enforced on modern trucks and buses.

### Features and Benefits

High output, low emission diesel engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers and turbochargers increase mechanical and thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and after-treatment devices all require improved oil performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with after-treatment devices. The advanced technology in Mobil Delvac XHP Ultra LE SCA 5W-30 delivers exceptional performance and protection of exhaust systems fitted with Diesel Particulate Filters. The key benefits include:

| Features   | Advantages and Potential Benefits   |
|--|---|
| Excellent protection against oil thickening, oil degradation, high temperature deposits and sludge build-up  | Contributes to long oil life consistent with OEM recommended Oil Drain Intervals (ODI)<br>Helps prevent ring sticking for better engine protection and efficiency   |
| Excellent protection against wear, scuffing, bore polishing and corrosion                                    | Helps control wear in heavy duty operation, promoting long engine life  |
| Excellent low temperature fluidity   | Contributes to excellent oil pumpability and circulation allowing operation in cold climate regions<br>Helps protect against wear during cold engine start-up   |
| Advanced "Low Ash" componentry   | Helps improve efficiency and extend durability of emission exhaust systems fitted with Diesel Particulate Filters (DPF)   |
| Advanced formulation viscometrics<br>. SAE 5W-30<br>. Stay-in-grade shear stability<br>. Very low volatility | Potentially helps to reduce fuel consumption over higher viscosity grade engine oils without compromising engine durability (potential fuel economy depending on vehicle type and driving conditions)<br>Helps to control viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions |

### Applications

Recommended by ExxonMobil for use in:

- This engine oil is specifically designed to meet the Scania LDF-4 specification
- In commercial vehicles where ACEA E6 or ACEA E7 is requested

- On-highway light and heavy-duty trucking
- Modern heavy-duty engines equipped with Diesel Particulate Filter (DPF) in line with owner manual recommendations

### Specifications and Approvals

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| ACEA E6   |
| ACEA E7   |
| Scania LDF-4  |

### Properties and Specifications

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-30 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 228       |
| Density @ 15 C, g/ml, ASTM D1298                           | 0.85      |
| Ash, Sulfated, mass%, ASTM D874                            | 1         |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 11.6      |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 69.5      |
| Pour Point, °C, ASTM D97                                   | -33       |
| Total Base Number, mgKOH/g, ASTM D2896                     | 10        |
| Viscosity Index, ASTM D2270                                | 162       |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Automotive products: 0800 0229118

Industrial products: 0800 0229120

Fax: 0800 0229222


Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is

intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved