



Mobilmet™ 760 Series

Mobil Industrial , Netherlands

Oil Based Cutting Fluids

Product Description

Mobilmet™ 760 Series are extra high performance neat cutting oils. They are chlorine-free and are intended for severe cutting operations especially on diffi machine steels. Mobilmet 760 Series oils are not recommended for use with copper and it's alloys due to its aggressiveness towards these softer yellow me comparison with other leading premium cutting oils, Mobilmet 760 Series oils have demonstrated superior surface finish, extended tool life and control of built-up Their light colour enables the work area to be seen during machining operations. Closer tolerances are consistently achieved. The oils are formulated to preve formation of oil mist in the vicinity of the machine tool, thus contributing to a safer and more pleasant working environment.

With the benefit of comprehensive development testing using modern machining equipment, plus extensive customer evaluations, Mobilmet 760 Series product: become the products of choice for many machine shops.

Features and Benefits

The Mobilmet brand of cutting fluids has gained a well-deserved reputation for innovation and outstanding performance over the years. The Mobilmet 760 Series important member of this family with their chlorine-free and low-misting additive technology. This formulation approach yields superb performance in a wide ra applications, while providing the environmental and disposal benefit of being chlorine-free.

Additional features and potential benefits of Mobilmet 760 products include:

Features	Advantages and Potential Benefits
Superb machining performance	Increased production resulting from longer tool life and reduced downtime for tool changes
	Improved surface finish, closer tolerances and reduced formation of built-up edge resulting in fewer rejects
Excellent lubricity	Cooler work pieces and increased feed rates possible for reduced operating costs
Broad multi-purpose capability	Suitability for a wide range of severe machining operations on difficult steels
Light transparent colour	Provides a clear view of the tool and work piece
Anti-mist formulation	Improved workplace safety

Applications

Mobilmet 760 Series are recommended for severe cutting operations on normal and difficult to machine steels. Specific applications, by grade, include:

- Mobilmet 762 is particularly suitable for drilling, deep hole drilling (less than 20 mm diameter), threading, tapping, parting-off and automatic lathe operati small work pieces
- Mobilmet 763 is recommended for deep hole drilling (greater than 20 mm diameter), drilling, tapping, threading, milling, gear shaping, broaching, parting-c automatic lathe operations
- Mobilmet 766 is used for tapping, threading, milling, gear shaving and shaping, broaching, planing, parting-off and automatic lathe operations

Properties and Specifications

Property	762	763	766
Chlorine, ppm, ASTM D6443	NIL	NIL	NIL

Property	762	763	766
Density @ 15 C, g/cm3, ASTM D4052	0.87	0.87	0.88
Flash Point, Cleveland Open Cup, °C, ASTM D92	160	180	205
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	3.0	4.0	6.0
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	10	18	36
Sulfur, Active, wt%, ASTM D1662	1.6	1.6	1.6

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021
EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Automotive products: 0800 0229118
Industrial products: 0800 0229120
Fax: 0800 0229222

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved