



Mobil Almo 500 Series

Mobil Industrial , New Zealand

Pneumatic Rock Drill and Tool Lubricants

Product Description

Mobil Almo 500 Series lubricants are premium quality high performance products primarily intended for the lubrication of pneumatically operated rock c underground and surface mining operations. The Mobil Almo Series oils are formulated from high quality base stocks and additives, which provide excellent ch stability and good protection against wear and corrosion. They offer an optimum balance of adhesiveness, yet are emulsifiable enough to pick up moisture carried air stream reducing the negative effects of water on wear and corrosion. They do not form gummy deposits that could cause sluggish valve action. Even in the pre of water, the Mobil Almo 500 Series oils have good preferential metal-wetting properties that maintain continuous oil films. These properties in combination with h characteristics help provide excellent lubrication resulting in long equipment life.

Mobil Almo 500 Series possess high viscosity indexes and low pour points to ensure good lubrication at the low temperatures resulting from air expansion and against icing stoppages while providing adequate films on drill parts that may operate at high temperatures. Oil fog generation levels are extremely low.

Features and Benefits

The Mobil Almo 500 Series oils provide an optimum performance balance which assures long equipment life and minimal maintenance costs. Their excellen protection characteristics and ability to provide adequate lubrication in the presence of water not only reduces wear but protects against rust and corrosion. Thei chemical stability prevents sludge and deposit formation reducing the need for frequent maintenance.

| Features | Advantages and Potential Benefits |
|--|--|
| Effective Chemical Stability | Reduce sludge and deposit formation Improves valve operation |
| Desired Emulsifiable Properties | Effective lubrication in presence of water |
| High Viscosity Index | Provides good lubrication at both high and low temperatures |
| Excellent Load Carrying Ability and Anti-Wear Protection | Reduces component wear Prolongs equipment life Reduces maintenance costs |
| Very Good Adhesive Characteristics | Protects metal surfaces from corrosion Provides good lubricant films under all conditions |
| Rust and Corrosion | Longer tool life Increased tool performance |

Applications

Mobil Almo 500 Series oils are recommended for use in all pneumatically operated rock drills in both underground and surface mining as well as in contractor and industrial applications. They are suitable for percussive- and rotary- type tools. The viscosity grades allow selection for year-round use where seasonal air temperature variations are extreme.

- Pneumatically operated rock drills in underground and surface mining operations
- Pneumatically operated drills and jack hammers in highway construction and building operations
- Rock drills in quarry operations
- Percussion and rotary air-operated tools in industrial applications

Typical Properties

| | Mobil Almo 524 | Mobil Almo 525 | Mobil Almo 527 | Mobil Almo 529 | Mobil Almo 530 | Mobil Almo 532 | Mobil Almo 534 |
|-----------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| ISO Viscosity Grade | 32 | 46 | | | 220 | 320 | 460 |
| Viscosity, ASTM D 445 | | | | | | | |

| | Mobil Almo 524 | Mobil Almo 525 | Mobil Almo 527 | Mobil Almo 529 | Mobil Almo 530 | Mobil Almo 532 | Mobil Almo 534 |
|--------------------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| cSt @ 40° C | 32 | 46 | 112.9 | 172 | 220 | 320 | 460 |
| cSt @ 100° C | 5.5 | 7.3 | 11.4 | 16.5 | 19.7 | 24.9 | 32 |
| Viscosity Index, ASTM D 2270 | 108 | 105 | 91 | 102 | 100 | 99 | 99 |
| Pour Point, °C, ASTM D 97 | -51 | -30 | -27 | -24 | -24 | -21 | -30 |
| Flash Point, °C, ASTM D 92, min | 170 | 188 | 204 | 220 | 220 | 232 | 239 |
| Density @ 15.6° C, ASTM D 4052, kg/L | 0.880 | 0.883 | 0.899 | 0.893 | 0.893 | 0.902 | 0.901 |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Switzerland Use: Toxicity class: free BAG T No.: 611500

The Mobil logotype, the Pegasus design and Almo are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020
Mobil Oil New Zealand Limited
164-188 Beaumont St
Auckland
New Zealand

+ 64 4 498 4000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved