



## Mobil Delvac 25W-60

Mobil Commercial Vehicle Lube , Peru

High Performance Diesel Engine Oil

### Product Description

Mobil Delvac™ 25W-60 is a high viscosity, high performance diesel engine oil that provides proven protection for diesel engines operating in severe service applications.

Mobil Delvac™ 25W-60 is formulated from quality base stocks combined with performance additives, which help protect against the formation of sludge and corrosion.

### Features and Benefits

- Helps to reduce engine wear and corrosion in higher mileage vehicles
- Protects under a wide variety of operating conditions, especially high temperatures
- Helps reduce oil leakage due to the thick oil film
- Reduce oil consumption

### Applications

Mobil Delvac™ 25W-60 is recommended by ExxonMobil for higher mileage vehicles including turbo charged, super charged, fuel injected, multi-valve and normally aspirated engines.

Before using Mobil Delvac™ 25W-60, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF-4

<b>This product meets or exceeds the requirements of:</b>
API SL
API SJ

### Properties and Specifications

<b>Property</b>	
-----------------	--

Property	
Grade	SAE 25W-60
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	246
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	22.9
Pour Point, °C, ASTM D97	-16
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	215
Total Base Number, mgKOH/g, ASTM D2896	8.2
Viscosity Index, ASTM D2270	115
Density @ 15 C, g/ml, ASTM D1298	0.89

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2020

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud      LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved