



Mobil™ Monogrado 40

Mobil Passenger Vehicle Lube , Peru

Mobil passenger-vehicle-lube

Product Description

Mobil™ Monogrado 40 is a heavy duty motor oil designed primarily for use in passenger car gasoline engines. It is formulated from high quality mineral base oils and an advanced additive system required for combustion engines where an API SL motor oil is recommended. Contains an effective balance of detergents and dispersants to minimize sludge and deposit formation, retain alkalinity (TBN), and reduce wear.

Features and Benefits

- Helps promote engine cleanliness.
- Good protection against wear and corrosion.
- Extended intervals between oil drains.
- Low oil consumption.

Applications

Mobil Monogrado 40 is recommended for the lubrication of gasoline engines for passenger cars. It can also be used in hydraulic and gear applications if the manufacturer approves the use of monograde motor oils for these applications.

Specifications and Approvals

This product is recommended for use in applications requiring:
API SG
API SH

This product meets or exceeds the requirements of:
API SJ
API SL

Properties and Specifications

Property	
Grade	SAE 40
Density @ 15 C, g/ml, ASTM D1298	0.89

Property	
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	218
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.9
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	150.7
Pour Point, °C, ASTM D97	-17

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

Terpel Comercial del Perú S.R.L.

Av. Camino Real 456,

Torre Real Piso 14 San Isidro

Lima Perú

24 Horas emergencia en salud LUBES (511)- 222 0284

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved