



Mobil Delvac XHP ESP M 10W-40

Mobil Commercial Vehicle Lube , Poland

Emission System Protection Diesel Engine Oil

Product Description

Mobil Delvac XHP ESP M 10W-40 is a synthetic extra high performance diesel engine oil engineered to provide lubrication to modern, high performance, low emissions engines used in severe applications. This engine oil is designed using high performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control. The new advanced additive system has been expertly engineered to help towards long engine life and maintain the efficiency of emission reduction systems including the Diesel Particulate Filter (DPF). Its specifications and approvals allow Mobil Delvac XHP ESP M 10W-40 to target mixed fleet applications.

Features and Benefits

High output, low emission engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and aftertreatment devices all require improved oil performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with aftertreatment devices. The advanced technology in Mobil Delvac XHP ESP M 10W-40 delivers exceptional performance, long drain interval capability and protection of exhaust systems including those fitted with Diesel Particulate Filters (DPF). The key benefits include:

Features	Advantages and Potential Benefits
Outstanding protection against oil thickening, high temperature deposits, sludge build-up and, oil degradation	Provides capability for long drain intervals Helps to protect against ring sticking
Excellent anti-wear, anti-scuff properties and bore polishing and corrosion protection	Helps to towards long engine life*
Stay-in-grade shear stability. Very low volatility	Helps to reduce viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions
Low ash, sulfur and phosphorous levels	Helps to protect exhaust systems devices like those fitted with DPF
Excellent low temperature properties	Helps to improve pumpability and oil circulation
	*Well formulated oils, like Mobil Delvac, that meet or exceed industry or OEM specifications, can help protect engines. Consult OEM for optimum fluid selection. Actual results may vary depending on OEM requirements, type of engine and its maintenance, application and service conditions, and prior lubricant used.

Applications

- Heavy Duty Diesel Engines including Euro V/VI Modern Low Emissions Vehicles, Utilizing Technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR)
- Heavy Duty Diesel Engines using low sulfur diesel fuels and many biodiesel fuel formulations
- Naturally Aspirated and Turbo-Charged Diesel Powered Equipment
- On-Highway Short-Haul and Long-Haul Trucks and Buses
- Off-Highway Mining, Construction and Agricultural Equipment

Specifications and Approvals

This product has the following approvals:

MAN M 3477

MAN M 3271-1

MTU Oil Category 3.1

VOLVO VDS-4

VOLVO VDS-3

RENAULT TRUCKS RLD-3

RENAULT TRUCKS RLD-2

DEUTZ DQC IV-10 LA

AVTO DIESEL (YaMZ)YaMZ-7-17

Mack EO-O Premium Plus

This product is recommended for use in applications requiring:

MAN M 3575

SCANIA SCANIA LOW ASH

This product meets or exceeds the requirements of:

API CJ-4

API CI-4 PLUS

API CI-4

JASO DH-2

DAF Extended Drain

Cummins CES 20081

CATERPILLAR ECF-3

ACEA E4

ACEA E6

ACEA E7

ACEA E9

ISUZU DEO (w/ DPD Equipped Vehicles)

Properties and Specifications

Property	
Grade	SAE 10W-40
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	89.3
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.8
Viscosity Index, ASTM D2270	157
Ash, Sulfated, mass%, ASTM D874	1.0
Total Base Number, mgKOH/g, ASTM D2896	12.8
Pour Point, °C, ASTM D97	-36
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Density @ 15 C, kg/m ³ , ASTM D4052	0.860

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland sp. z o.o.

ul.Chmielna 85/87

00-805 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon

Mobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved