



Mobilcut 240
Mobil Industrial , Poland
Aqueous Metal Working Fluid with innovative technology

Product Description

Mobilcut 240 is a premium quality semi synthetic water miscible metalworking fluid. It is based on innovative technology that offers some outstanding adva including hard water compatibility, machine tool cleanliness and long term stability. Mobilcut 240 is free from added boron and boric acid, hence meeting the Health and Safety related trends.

Mobilcut 240 is formulated using high quality mineral oils and a carefully selected blend of emulsifiers. When mixed with water of hardness 60 °dH or le concentrate produces stable, translucent emulsions.

Having a relatively low oil content, Mobilcut 240 provides excellent wetting and detergency and superb cooling and cutting properties, making it suitable for l moderate duty cutting and grinding applications. It also offers low foam potential and long-term corrosion protection for machine and components. It also helps si machine shop productivity by requiring low maintenance and providing a long term stability.

Features and Benefits

Mobilcut 240 is designed to help increase the productivity of modern machine shops by offering high performance features whilst meeting the latest Health and trends.

Features	Advantages and Potential Benefits
Outstanding water hardness acceptance	Problem solver in hard water applications
Superb flushing ability	Clean machines even with problematic workpieces
Forms no residues during operation	Improves machine cleanliness
Easy re-emulsification of dry residues after start-up	Less cleaning effort
Boron free	Will comply future legislation.
Low care and maintenance	Extended batch life and reduction of unpleasant odors
High buffer capacity	Stable pH without additional maintenance
Low foaming potential	Improved performance even in high pressure systems
High degree of corrosion protection	Reduces machine maintenance and rework of materials
Good separability from fines	Improves filterability and surface finish
Wide Range of applicability	Potential to consolidate products and reduce inventories
Compatible with slideway lubricants	Separation and removal of tramp oil
Neutral Odor	Enhances the workplace environment

Applications

Mobilcut 240 is a universal metalworking fluid and is suitable for a range of light to moderate duty cutting and grinding applications on ferrous metals in both cent or individual machines.

Mobilcut 240's outstanding flushing ability makes it particularly recommended for the machining and grinding of cast iron and while helping to maintain m cleanliness. It is not suitable for the general machining of aluminium and its alloys.

Operations / Recommended Dilutions

Mobilcut 240 is designed for dilutions between 4% and 10%.

The table below offers approximate dilutions for general applications.

	Cast Iron	Carbon Steel	Alloy Steel	Yellow Metal
--	-----------	--------------	-------------	--------------

	Cast Iron	Carbon Steel	Alloy Steel	Yellow Metal
Grinding	4,0 % - 6,0 %	5,0 % - 6,0 %	5,0 % - 6,0 %	limited usage
Milling	5,0 % - 7,0 %	6,0 % - 8,0 %	6,0 % - 8,0 %	limited usage
Turning	5,0 % - 7,0 %	6,0 % - 8,0 %	6,0 % - 8,0 %	limited usage
Drilling	6,0 % - 8,0 %	8,0 % - 10,0 %	8,0 % - 10,0 %	limited usage

Typical Properties

Mobilcut 240	
Appearance (Concentrate)	Clear, orange Liquid
Appearance (Emulsion)	Translucent
Emulsion Type	Semi-synthetic
Mineral Oil Content (Concentrate)	20%
Refractometer Correction Factor	1.70 (Brix)
pH @ 5% in DIN 20 Water (Emulsion)	9.1
Density @ 15°C / 59°F (Concentrate)	995 kg/m ³
Kin. Viscosity @ 20°C / 68°F (Concentrate)	110 mm ² /s approx.
Pour Point (Concentrate)	< -10°C
Corrosion Protection: DIN 51360/I @ 4% DIN 51360/II @ 5%	R0/S0 – no corrosion 0/1 – no corrosion
Hard Water Stability @ 5% in 60° dH Water	no oil, no creaming, minimal Calcium soap formation
Salt Water Stability @ 5% plus 0.5% NaCl	Stable, no creaming

Health and Safety

Classified WGK 2 in Germany.

Stable when stored at 10 °C/50 °F to 25 °C/77 °F in unopened container for up to 12 months. Avoid frost where possible.

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Mobilcut are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

01-2020

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BV.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

ExxonMobil Poland Sp. z o.o.

Al. Jerozolimskie 98

00-807 Warszawa

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.pl/pl-pl/contact-us>

Tel +48 22 556 29 00

Fax +48 22 620 16 61

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended

override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTOMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved