



## Mobil Super™ 2000 x3 5W-40

Mobil Passenger Vehicle Lube , Russia

Premium Semi-Synthetic Passenger Vehicle Engine Oil - Everyday Protection

### Product Description

Mobil Super™ 2000 x3 5W-40 is a synthetic technology engine oil that provides everyday protection against wear and sludge to ensure long engine life.

### Product Benefits

Mobil Super 2000 products are industry proven, so you can trust your engine will get the protection it needs. Mobil Super 2000 x3 5W-40, confidence in every journey, provides multiple benefits:

- Reliable wear protection
- High level of sludge prevention
- Engine long life and cleanliness
- Cold start-up protection
- Reliable high temperature protection

### Applications

ExxonMobil recommends Mobil Super 2000 x3 5W-40 for:

- Older engine technologies
- Gasoline and Diesel without Diesel Particulate Filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions

### Specifications and Approvals

<b>This product has the following approvals:</b>
AVTOVAZ (LADA cars)
MB-Approval 229.3
VW 502 00
VW 505 00

<b>This product meets or exceeds the requirements of:</b>
ACEA A3/B4
API SN PLUS
AAE (STO 003) Group B7

**This product meets or exceeds the requirements of:**

ACEA A3/B3

### Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	80.8
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.2
Viscosity Index, ASTM D2270	165
Pour Point, °C, ASTM D97	-39
Phosphorus, mass%, ASTM D4951	0.10
Ash, Sulfated, mass%, ASTM D874	1.0
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Density @ 15 C, g/ml, ASTM D1298	0.859

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

Mobil Oil Lubricants LLC : 123242, Moscow, Novinsky boulevard, 31, Russia

+ 7 (095) 232 22 23

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.ru/ru-ru/contact-us-technical>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExonMobil**



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved