



Mobil Delvac MX™ 15W-40

Mobil Commercial Vehicle Lube , Thailand

Synthetic Technology Commercial Vehicle Engine Oil

Product Description

Mobil Delvac MX 15W-40 is an extra high performance diesel engine oil that provides excellent lubrication of today's diesel engines promoting extended engine life. As a result, this product meets or exceeds the specifications of virtually all major European and American engine manufacturers. This extra high performance has been proven in the field in a wide variety of industries, applications, and mixed fleets.

The advanced chemistry of this product provides outstanding performance in both modern, demanding low-emission diesel engines and older diesel engines operating on low or high sulphur fuel. Mobil Delvac MX 15W-40 is a biodiesel compatible* and combines a blend of high performance base stocks with a progressive additive system to provide superior control of oil thickening due to soot build-up and high temperatures as well as outstanding resistance to oxidation, corrosion, and high temperature deposits.

*based on CEC L-109-14 (test modified with palm B100), meeting the limits in ACEA E7-16

Features and Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Top piston fire rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase thermal stress on the lubricant. Increased fuel injector pressure and retarded timing improve fuel burn efficiency, but also increase engine temperatures and increase soot loads. Mobil Delvac MX 15W-40 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Cleaner engines and longer component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Longer gasket and seal life
Meets demanding specifications of key OEMs	One engine oil for mixed fleet operations

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from leading Japanese, European, and American manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying, and agriculture
- Mixed fleet applications

Specifications and Approvals

This product has the following approvals:

Mack EO-M Plus

Mack EO-N

MB-Approval 228.3

MTU Oil Category 2

RENAULT TRUCKS RLD-2

VOLVO VDS-3

This product is recommended for use in applications requiring:

ACEA A2

ACEA B2

API CG-4

API CF-4

API CF

Cummins CES 20072

Cummins CES 20071

Detroit 7SE 270 (4-STROKE CYCLE)

Mack EO-M

RENAULT TRUCKS RLD

VOLVO VDS-2

This product meets or exceeds the requirements of:

API CI-4

API CH-4

API SL

API SJ

CATERPILLAR ECF-2

Cummins CES 20078

Cummins CES 20077

This product meets or exceeds the requirements of:

Cummins CES 20076

ISUZU DEO (w/o DPD Equipped Vehicles)

JASO DH-1

ACEA E7

Properties and Specifications

Property	
Grade	SAE 15W-40
Ash, Sulfated, mass%, ASTM D874	1.3
Density @ 15.6 C, g/ml, ASTM D4052	0.885
Flash Point, °C, ASTM D92	228
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.4
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	106
Pour Point, °C, ASTM D97	-30
Total Base Number, mgKOH/g, ASTM D2896	12
Viscosity Index, ASTM D2270	140

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

Esso (Thailand) Public Company Limited
3195/17-29 Rama IV Road
Klong Tan, Klong Toey District
Bangkok 10110
Thailand

+66 2 2624 000


<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved