



Mobil 1™ FS 5W-40

Mobil Passenger Vehicle Lube , Ukraine

Advanced Fully Synthetic Engine Oil

Product Description

Mobil 1™ is the world's leading synthetic engine oil brand delivering our ultimate performance and protection. The Mobil 1 technology keeps your engine running like new. Mobil 1™ FS 5W-40 is an advanced performance synthetic engine oil designed to help provide exceptional cleaning power.

Features and Benefits

Mobil 1™ FS 5W-40 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing :

* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

- Engine wear protection and lubrication over the full oil drain interval.
- Excellent protection for your engine by helping to prevent the buildup of harmful deposits
- Enhanced cleaning technology for cars with higher mileage; 100 000km +
- Improved protection against variable fuel quality*
- Protection for your engine during start-up at low temperatures

Applications

Mobil 1 FS 5W-40 is recommended for many types of vehicles with higher mileage; > 100 000 km

- To be used for high performance engines in Volkswagen, Audi, Skoda, Porsche, Mercedes Benz and other cars requiring the specifications and approvals listed below

Specifications and Approvals

This product has the following approvals:
AVTOVAZ (LADA cars)
RENAULT RN0700
RENAULT RN0710
MB-Approval 229.5
FIAT 9.55535-M2

This product is recommended for use in applications requiring:

API CF

FIAT 9.55535-M2

This product meets or exceeds the requirements of:

AAE (STO 003) Group B7

API SJ

API SL

API SM

API SN

ACEA A3/B3

ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.5
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	5000
Total Base Number, mgKOH/g, ASTM D2896	12.5
Pour Point, °C, ASTM D97	-45
Noack Volatility, mass%, ASTM D5800	7.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved